

# 现货供应 PA66 美国杜邦 70G33HS1L BK031 黑色玻纤增强33%热稳定

产品名称	现货供应 PA66 美国杜邦 70G33HS1L BK031 黑色玻纤增强33%热稳定
公司名称	京冀(广州)新材料有限公司
价格	27.00/千克
规格参数	PA66:70G33HS1L BK031 黑色 70G33H:玻纤增强33% 美国杜邦:热稳定
公司地址	广州市南沙区丰泽东路106号(自编1号楼)X130 1-E014087(注册地址)
联系电话	18938547875 18938547875

## 产品详情

供应黑色耐热PA66/美国杜邦/70G33HS1L BK031标准产品

Zytel70G33HS1L BK031是一种33%玻纤增强，热稳定，黑色尼龙66树脂注塑成型。Zytel 70G33HS1L BK031

NYLON RESIN

33%玻璃纤维增强材料

填料/增强材料

玻璃纤维增强材料, 33%填料按重量

添加剂

热稳定剂

性能特点

超声波可焊接

良好的抗蠕变性

热稳定性

热稳定性

热稳定性，良好

用途

电气/电子应用领域

工业领域：

家电部件

汽车领域的应用：

Zytel PA66:

101: General purpose polyamide 66 resin for injection molding and extrusion(通用聚酰胺66树脂注塑成型和挤出)

101F: Internally lubricated polyamide 66 resin for injection molding. It was developed for fast cycles and high productivity.(含有润滑聚酰胺66树脂注塑。它是为快速周期和\*\*\*)

101L: Lubricated polyamide 66 resin for injection molding ( 润滑聚酰胺66树脂注塑成型 )

103FHS: Heat stabilized, internally lubricated polyamide 66 resin for injection molding. It was developed for fast cycles and high productivity. ( 热稳定，国内聚酰胺66树脂注塑润滑。它是为快速周期和\*\*\* )

103HSL: Heat stabilized, lubricated polyamide 66 resin for injection molding ( 热稳定，聚酰胺66树脂注塑润滑 )

151L: Lubricated, general purpose molding grade ( 润滑，通用品级 )

158L: Lubricated, general purpose molding/extrusion grade -- a higher melt viscosity than Zytel 151L NC010 ( 润滑，通用注塑/挤出级-高熔体比Zytel151L NC010粘度 )

153HSL: Lubricated, heat stabilized, extrusion grade ( 润滑，热稳定，挤出级 )

114HSL: heat stabilized, lubricated, modified polyamide 66 resin for injection molding. (热稳定，润滑，改性聚酰胺66树脂注塑)

132F: Nucleated, lubricated polyamide 66 for injection molding. It is suitable for fast production cycles and high productivity applications (核，润滑尼龙66注塑成型。它适用于快速的生产周期和\*\*\*应用的理想选择)

135F: Zytel 135F is a nucleated polyamide 66 resin for injection molding. It was developed for fast cycles and high productivity. (Zytel135F是一个有核的聚酰胺66树脂注塑。它是为快速周期和\*\*\*)

145: Zytel 145 BK010 is a weather resistant, high flow, fast cycling, modified polyamide 66 resin with improved toughness. (Zytel 145 BK010是耐候性，高流动性，快速循环，聚酰胺66树脂改性，改善韧性。)

157HSL: Lubricated, heat stabilized, improved weather resistant molding/extrusion grade (润滑，热稳定，提高耐候成型/挤出级)

330: Transparent nylon resin(透明尼龙树脂)

42A: Zytel 42A NC010 is a high viscosity polyamide 66 resin for injection molding and extrusion.(Zytel42A是一种聚酰胺66树脂注塑成型和挤压高粘度)

450HSLX: Zytel 450HSLX is a heat stabilized, lubricated, medium toughened polyamide 66 for injection molding. It has high impact resistance at low temperature and dry as molded.(Zytel450HSLX是一种热稳定，润滑，中等增韧尼龙66注塑成型。它在低温高抗冲击性和干燥)

45HSB: High viscosity, heat stabilized polyamide 66 resin for injection molding and extrusion applications such as film and tubing.(高粘度，热稳定尼龙注塑成型，如电线和管材挤出应用66树脂)

70G13: 13% Glass fiber reinforced polyamide 66 resin for injection molding (13%玻璃纤维增强聚酰胺66树脂注塑成型)

70G33: 33% Glass fiber reinforced polyamide 66 resin for injection molding (33%玻璃纤维增强聚酰胺66树脂注塑成型)

70G43: 43% Glass fiber reinforced polyamide 66 resin for injection molding (43%玻璃纤维增强聚酰胺66树脂注塑成型)

70G43L: 43% Glass fiber reinforced polyamide 66 resin for injection molding (43%玻璃纤维增强聚酰胺66树脂注塑成型)

70G13HS1L: 13% Glass fiber reinforced, heat stabilized, polyamide 66 resin for injection molding ( 13% 玻璃纤维增强 , 热稳定 , 聚酰胺66树脂注塑成型 )

70G13L: 13% Glass fiber reinforced polyamide 66 resin for injection molding ( 13% 玻璃纤维增强聚酰胺66树脂注塑成型 )

70G25HSLR: 25% Glass fiber reinforced, heat stabilized, hydrolysis resistant polyamide 66 resin for injection molding ( 25% 玻璃纤维增强 , 热稳定 , 抗水解聚酰胺66树脂注塑成型 )

70G30HSL: Zytel 70G30HSL is a 30% glass reinforced, heat stabilized, black nylon 66 resin for injection molding. ( Zytel 70G30HSL 是一个 30% 的玻璃纤维增强 , 热稳定 , 注塑成型的黑色尼龙66树脂 )

70G30HSLR : 30% Glass fiber reinforced, heat stabilized, hydrolysis resistant polyamide 66 resin for injection molding ( 30% 玻璃纤维增强 , 热稳定 , 抗水解聚酰胺66树脂注塑成型 )

70G30HSR2 : Zytel 70G30HSR2 is a 30% glass fiber reinforced, heat stabilized, hydrolysis resistant, black polyamide 66 resin for injection molding. ( Zytel 70G30HSR2 是一个 30% 的玻璃纤维增强 , 热稳定 , 抗水解 , 黑色尼龙66树脂注塑 )

70G30L : 30% Glass fiber reinforced polyamide 66 resin for injection molding.  
( 30% 玻璃纤维增强聚酰胺66树脂注塑 )

70G33GRA : 33% Glass fiber reinforced(33% 玻璃纤维增强)

70G33HS1L : 33% Glass fiber reinforced, heat stabilized polyamide 66 resin for injection molding(33% 玻璃纤维增强 , 热稳定聚酰胺66树脂注塑成型 )

70G33L : 33% Glass fiber reinforced polyamide 66 resin for injection molding(33% 玻璃纤维增强聚酰胺66树脂注塑成型 )

70G35HSL : 35% Glass fiber reinforced, heat stabilized polyamide 66 resin for injection molding(35% 玻璃纤维增强 , 热稳定聚酰胺66树脂注塑成型 )

70G35HSLRA4 : 35% Glass fiber reinforced, heat stabilized, hydrolysis resistant polyamide 66 resin for injection molding. It has excellent flow characteristics.  
( 35% 玻璃纤维增强 , 热稳定 , 抗水解聚酰胺66树脂注塑。它具有优异的流动特性。 )

70G35HSLX : Zytel 70G35HSLX is a 35% glass fiber reinforced, heat stabilized, black polyamide 66 for injection molding. ( Zytel 70G35HSLX 是一个 35% 的玻璃纤维增强 , 热稳定 , 注塑成型黑色尼龙66 )

70G43HSLA : 43% Glass fiber reinforced, heat stabilized, black polyamide 66 resin for injection molding.(43%玻璃纤维增强，热稳定，用于注射成型的黑色尼龙66树脂。)

70G43L : 43% Glass fiber reinforced polyamide 66 resin for injection molding ( 43%玻璃纤维增强聚酰胺66树脂注塑成型 )

70G50HSLA : 50% Glass fiber reinforced, heat stabilized polyamide 66 resin for injection molding. It has excellent flow characteristics. ( 50%玻璃纤维增强，热稳定聚酰胺66树脂注塑。它具有优异的流动特性。)

70G60HSL : Zytel 70G60HSL is a 60% glass fiber reinforced, heat stabilized, lubricated polyamide 66 for injection molding. ( Zytel70G60HSL为60%的玻璃纤维增强，热稳定，润滑尼龙66注塑成型 )

70K20HSL : Aramid-modified, heat stabilized, lubricated PA66 resin with excellent wear resistance. ( 芳纶改性，热稳定，润滑尼龙66树脂具有优良的\*\*\*性 )

75CG30HSL : Zytel 75CG30HSL is a glass-reinforced, toughened, heat stabilized polyamide resin modified with carbon fiber for improved performance in structural applications. ( Zytel75CG30HSL是一种玻璃纤维增强，增韧，热稳定聚酰胺树脂结构与碳纤维改性应用的性能。)

75LG40HSL : Zytel 75LG40HSL is a 40% long glass reinforced, heat stabilized, lubricated polyamide 66 resin for structural applications. ( Zytel75LG40HSL是40%长玻璃纤维增强，热稳定，聚酰胺66树脂润滑结构的应用 )

75LG50L: Zytel 75LG50L is a 50% long glass reinforced, lubricated polyamide 66 resin for structural applications.(Zytel75LG50L是50%长玻璃纤维增强聚酰胺66树脂润滑结构的应用)

75LG50HSL: Zytel 75LG50HSL is a 50% long glass reinforced, heat stabilized, lubricated polyamide 66 resin for structural applications. ( Zytel75LG50HSL50%的长玻璃纤维增强，热稳定，聚酰胺66树脂润滑结构的应用 )

75LG60HSL: Zytel 75LG60HSL is a 60% long glass reinforced, heat stabilized, lubricated polyamide 66 resin for structural applications. ( Zytel75LG60HSL为60%长玻璃纤维增强，热稳定，聚酰胺66树脂润滑结构的应用 )

东莞市京冀塑胶原料有限公司是一般纳税人企业，公司以专业人才为主体，集研发，销售为一体的企业。公司位于中国塑胶重镇东莞樟木头镇塑胶中心城，公司利用自身专业优势积极开发业务，辐射全国各地，在\*\*\*和同行树立了良好的\*\*\*信誉，并不断提高对客户的服务质量水平。

我们的宗旨：合作求共赢！顾客至上，\*\*\*，竭诚服务，原厂原包，质量\*\*\*、\*\*\*，货源稳定、可开增值税发票，可随货提供PPO报告、UL认证、材质证明及物性安全资料表等相关信息

温馨提示:

如您未找到合适的型号，或者有工程技术方面的疑问，可以随时来电至我司咨询，我司将有专业工程师替您解答疑惑

本公司货源充足，品种\*\*\*，\*\*\*。

另有其他原料牌号无法详细介绍，具体事宜（随货提供：物性、报价、UL报告、RoSH标准、等.）

测报告、物质安全表MSDS、FDA认证以及原料物性表等等）敬请来函来电联系！

注：产品图片不代表实际包装，请以实际为准。

由于"价格"浮动,请您及时来电,旺得福塑胶给你"报价"!!