

# 和泉继电器RJ2S-CL-D24V

产品名称	和泉继电器RJ2S-CL-D24V
公司名称	乐清市立启电气厂
价格	15.00/个
规格参数	应用范围:中间 品牌:idec/和泉 型号:rj2sdc24v
公司地址	浙江乐清市柳市岙外工业区
联系电话	86 0577 62706991

## 产品详情

rj1s-cl-a12,rj1s-cl-a24,rj1s-cl-a110,rj1s-cl-a120,rj1s-cl-a220,rj1s-cl-a230

rj1s-cl-a240,rj1s-cl-d12,rj1s-cl-d24,rj1s-cl-d48,rj1s-cl-d100,rj1s-c-a12

rj1s-c-a24,rj1s-c-a110,rj1s-c-a120,rj1s-c-a220,rj1s-c-a230,rj1s-c-a240,rj1s-c-d12,rj1s-c-d24,rj1s-c-d48,rj1s-c-d100,rj1s-cld-d12,rj1s-cld-d24,rj1s-cld-d48,rj1s-cld-d100,rj1s-cd-d12,rj1s-cd-d24,rj1s-cd-d48,rj1s-cd-d100,rj1s-cld1-d12,rj1s-cld1-d24,rj1s-cld1-d48,rj1s-cld1-d100,rj1s-cld1-d12,rj1s-cld1-d24,rj1s-cld1-d48,rj1s-cld1-d100,rj1s1-cd-d12,rj1s-cd1-d24,rj1s-cd1-d48

rj1s-cd1-d100,rj1s-clr-a110,rj1s-clr-a120,rj1s-clr-a220,rj1s-clr-a230,rj1s-clr-a240,rj1s-cr-a110,rj1s-cr-a120,rj1s-cr-a220,rj1s-cr-a230,rj1s-cr-a240

rj2s-cl-a12,rj2s-cl-a24,rj2s-cl-a110,rj2s-cl-a120,rj2s-cl-a220,rj2s-cl-a230

rj2s-cl-a240,rj2s-cl-d12,rj2s-cl-d24,rj2s-cl-d48,rj2s-cl-d100,rj2s-c-a12,rj2s-c-a24,rj2s-c-a110,rj2s-c-a120,rj2s-c-a220,rj2s-c-a230,rj2s-c-a240,rj2s-c-d12,rj2s-c-d24,rj2s-c-d48,rj2s-c-d100,rj2s-cld-d12,rj2s-cld-d24,rj2s-cld-d48,rj2s-cld-d100,rj2s-cd-d12,rj2s-cd-d24,rj2s-cd-d48,rj2s-cd-d100,rj2s-cld1-d12,rj2s-cld1-d24,rj2s-cld1-d48,rj2s-cld1-d100,rj2s-cd1-d12,rj2s-cd1-d24,rj2s-cd1-d48,rj2s-cd1-d100,rj2s-clr-a110,rj2s-clr-a200,rj2s-clr-a220,rj2s-clr-a230,rj2s-clr-a240,rj2s-cr-a110,rj2s-cr-a200,rj2s-cr-a220,rj2s-cr-a230,rj2s-cr-a240

ru系列参数如下:高性能通用小型继电器,适应环保要求的设计.触点容量为,10a(ru2),6a(ru4),3a(ru42).型号如下:

ru2s-a24,ru2s-a100,ru2s-a110,ru2s-a200,ru2s-a220,ru2s-d6,ru2s-d12,ru2s-d24,ru2s-d48,ru2s-d110,ru2s-r-a100,ru2s-r-a110.ru2s-r-a200.ru2s-r-a220,ru2s-d-d6,ru2s-d-d12,ru2s-d-d24,ru2s-d-d48,ru2s-d-d110,ru2s-d1-d24,ru2s-c-a24

ru2s-c-a100,ru2s-c-a110,ru2s-c-a200,ru2s-c-a220,ru2s-c-d6,ru2s-c-d12,ru2s-c-d24,ru2s-c-d48,ru2s-c-d110,ru2s-cr-a100,ru2s-cr-a110.ru2s-cr-a200,ru2s-cr-a220,ru2s-cd-d6,ru2s-cd-d12,ru2s-cd-d24,ru2s-cd-d48,ru2s-cd-d110,ru2s-cd1-d24,ru2s-nf-a24,ru2s-nf-a100,ru2s-nf-a110,ru2s-nf-a200,ru2s-nf-a220

ru2s-nf-d6,ru2s-nf-d12,ru2s-nf-d24,ru2s-nf-d48,ru2s-nf-d110,ru2v-nf-a24

ru2v-nf-a100,ru2v-nf-a110,ru2v-nf-a200,ru2v-nf-a220,ru2v-nf-d6,ru2v-nf-d12,ru2v-nf-d24,ru2v-nf-d48,ru2v-nf-d110,ru4s-a24,ru4s-a100,ru4s-a110,ru4s-a200,ru4s-a220,ru4s-d6,ru4s-d12.ru4s-d24.ru4s-d48,ru4s-d110,ru4s-r-a100

ru4s-r-a110,ru4s-r-a200,ru4s-r-a220,ru4s-d-d6,ru4s-d-d12,ru4s-d-d24,ru4s-d-d48,ru4s-d-d110,ru4s-d1-d24,ru4s-c-a24,ru4s-c-a100,ru4s-c-a110,ru4s-c-a200,ru4s-c-a220,ru4s-c-d6,ru4s-c-d12,ru4s-c-d24,ru4s-c-d48,ru4s-c-d110,ru4s-cr-a100,ru4s-cr-a110,ru4s-cr-a200,ru4s-cr-a220,ru4s-cd-d6,ru4s-cd-d12

ru4s-cd-d24,ru4s-cd-d48,ru4s-cd-d110,ru4s-cd1-d24,ru4s-nf-a24,ru4s-nf-a100,ru4s-nf-a110,ru4s-nf-a200,ru4s-nf-a220,ru4s-nf-d6,ru4s-nf-d12,ru4s-nf-d24,ru4s-nf-d48,ru4s-nf-d110,ru4v-nf-a24,ru4v-nf-a100,ru4v-nf-a110,ru4v-nf-a200,ru4v-nf-a220,ru4v-nf-d6,ru4v-nf-d12,ru4v-nf-d24,ru4v-nf-d48,ru4v-nf-d110,ru42s-a24,ru42s-a100,ru42s-a110,ru42s-a200,ru42s-a220.ru42s-d6,ru42s-d12,ru42s-d24,ru42s-d48,ru42s-d100,ru42s-d110,ru42s-r-a100,ru42s-r-a110,ru42s-r-a200,ru42s-r-a220,ru42s-d-d6,ru42s-d-d12,ru42s-d-d24,ru42s-d-d48

ru42s-d-d100,ru42s-d-d110,ru42s-d1-d24,ru42s-c-a24,ru42s-c-a100,ru42s-c-a110,ru42s-c-a200,ru42s-c-a220,ru42s-c-d6,ru42s-c-d12.ru42s-c-d24,ru42s-c-d48,ru42s-c-d100,ru42s-c-d110,ru42s-cr-a100,ru42s-cr-a110,ru42s-cr-a200,ru42s-cr-a220,ru42s-cd-d6,ru42s-cd-d12,ru42s-cd-d20,ru42s-cd-d48,ru42s-cd-d100,ru42s-cd-d110,ru42s-cd1-d24,ru42s-nf-a24,ru42s-nf-a100,ru42s-nf-a11,ru42s-nf-a200,ru42s-nf-a220,ru42s-nf-d6.ru42s-nf-d12.ru42s-nf-d24.ru42s-nf-d48.ru42s-nf-d100.ru42s-nf-d110

rr系列参数如下:大功率型继电器,大容量10a-1.2及3极。型号有:

rr1ba-u, rr1ba-ul, rr1ba-uc, rr1ba-ulc, rr1ba-us, rr2p-u, rr2p-ul, rr2p-uc, rr2p-ulc, rr2ba-u, rr2ba-ul, rr2ba-uc, rr2ba-ulc, rr2ba-us, rr3p-u, rr3p-ul, rr3p-uc, rr3p-ulc, rr3b-u, rr3b-ul, rr3b-uc, rr3b-ulc, rr3b-us, rr3pa-u, rr3pa-ul, rr3pa-uc, rr3pa-ulc

rh系列参数如下: spdt~4pdt、10a触点小型功率继电器

rh1b-u, rh1b-ul, rh1b-ut, rh1b-ud, rh1v2-u, rh1v2-ud, rh2b-u, rh2b-ul, rh2b-uc, rh2b-ulc, rh2b-ut, rh2b-ud, rh2b-uld, rh2b-uld, rh2b-r, rh2b-lr, rh2v2-u, rh2v2-ul, rh2v2-ud, rh3b-u, rh3b-ul, rh3b-ut, rh3b-ulc, rh3b-d

rh3b-ld, rh3v2-u, rh3v2-ul, rh3v2-d, rh4b-u, rh4b-ul, rh4b-uc, rh4b-ulc

rh4b-ut, rh4b-ud, rh4b-ld, rh4v2-u, rh4v2-ul, rh4v2-ud

rm系列参数如下: dpdt触点(5a)具备插入式和pc板端子型。型号有:

rm2s-u, rm2s-ul, rm2s-uc, rm2s-ut, rm2s-ud, rm2s-uld, rm2v-u, rm2v-ul

ry系列参数如下:dpdt(3a)及4pdt(5a)触点具备双分叉型触点,型号有:

ry2s-u, ry2s-ul, ry2s-ut, ry2s-ud, ry22s-u, ry22s-ul. ry22s-ut, ry22s-ud, ry4s-u, ry4s-ul, ry4s-uc, ry4s-ulc, ry4s-ut, ry4s-ud, ry4s-uld, ry42s-u, ry42s-ul, ry42s-ut, ry42s-ud, ry2v-u, ry2v-ul, ry2v-ud, ry22v-u, ry22v-ul

ry22v-ud , ry4v-u , ry4v-ul , ry42v-u。 ry42v-ul

rr2kp系列参数如下：交替式闭锁继电器dpdt--触点容量10a。型号有：

rr2kp-u , rr2kp-uc

rh2l系列参数如下：小型功率闭锁继电器dpdt—触点容量10a。型号有：

rh2lb-u , rh2lv-u

ry2ks系列参数如下：交替式闭锁继电器dpdt—触点容量3a。型号有：

ry2ks-u , ry2ks-uc

my4nj ac110/120 by omzmy4nj ac220/240 by omzmy4nj-d2 dc24 by omzmy4nj-cr ac220/240 by omzmy4 ac200/220  
by ombmy4n ac220/240 by ombmy4j ac200/220 by ombmya-la12 ac200/220my2k dc24my2n-d2 dc24 (s)my2n-d2  
dc100/110 (s)my2n-cr ac220/240 (s)my2n-cr ac200/220 (s)my4n dc24 (s)my4n-d2 dc24 (s)my4n-cr ac220/240  
(s)my4n-cr ac200/220 (s)

欧姆龙其它型号产品欢迎来电查询!!谢谢

供应欧姆龙继电器mm2p , mm2xpn , mm4p , mm4xp产品名称：mm产品介绍：power relay接点安定信赖及长寿命power继电器 安装配线简单，使用容易

接点构成丰富，直流负载开关用，露出型依用途可选择

机械寿命500万次，电机寿命(额定负载时)50万次，长寿命

二极体内藏型及电力辅助继电器，依(tec-174d)标准，种类丰富产品类别：控制柜用mm2p ac220mm2p  
dc200/220mm2xp ac220mm2xp dc24mm2xp dc100/110mm2xp dc200/220mm2xp-d dc24mm2xpn dc24mm2xp-d  
dc200/220mm4p ac220mm4p dc200/220

本产品的 品牌为 IDEC/和泉，产品系列是 RJ2SDC24V，触点负载为 5a，触点切换电流是 5，触点切换电压为 250，触点形式是二开二闭，额定电流为 5a/250v，额定电压是 AC/DC24-240，防护特征为封闭式，线圈电源是 1，线圈功率为 1，型号是 RJ2SDC24V，应用范围为 中间，释放电流是 0.015，吸合电流为 0.015，电流性质是交流，