

放电管/GDT A007L_5.5x6.5_10A

产品名称	放电管/GDT A007L_5.5x6.5_10A
公司名称	无锡市超缘电子有限公司
价格	1.00/个
规格参数	品牌:超缘 型号:a007l_5.5x6.5_10a 种类:放电管
公司地址	无锡市北塘区凤翔北路27号三楼(7间)
联系电话	86 0510 66889162 13306173678

产品详情

features	applications
∅ extremely small size ∅ high current rating ∅ very fast response time ∅ stable performance over life ∅ very low capacitance ∅ high insulation resistance ∅ rohs-compatible	∅ modem ∅ xdsl-splitter ∅ data lines ∅ tuner ∅ antenna

electrical specifications

dc spark-over voltage1)	70 ± 20	
impulse spark-over voltage 1 kv/ μ s - for 99 % of measured values - typical values of distribution	< 600 < 550	
service life 10 operations 50 hz, 1 s 1 operations 50 hz, 0.18 s (9 cycles)	10 40	
10 operations 8/20 μ s 1 operation 8/20 μ s 1 operation 10/350 μ s	10 20 1	

300 operations	10/1000 μ s	100
insulation resistance at 50 vdc		> 1
capacitance at 1 mhz		< 2
weight		~ 1.5
operation and storage temperature		-40 ... +90
marking		cy 070
		cy - brand name
		70- nominal voltage

1) the voltage is measured with a low rate of rise $dv / dt = 100v/s$

dimensional drawing

	ordering code: a00715506000c
	not to scale
	dimensions in mm
	non controlled document

cautions and warnings

∅ surge arresters must not be operated directly in power supply networks. ∅ surge arresters may become hot in case of longer periods of current stress (danger of burning). ∅ surge arresters may be used only within their specified values. in case of overload, the head contacts may fail or the component may be destroyed. ∅ damaged surge arresters must not be re-used.

本产品的品牌为超缘，型号是 A007L_5.5x6.5_10A，种类为放电管，用途是计算机系统，体积为小型，电压特性是低压，形状为其他，熔断速度是 FF/特快速，执行标准为国标，自动复位功能是有，