

漆包线 qz qa qzy

产品名称	漆包线 qz qa qzy
公司名称	上海烨发机电设备有限公司
价格	70.00/千克
规格参数	品牌:兴达 型号:qzqaqzy 绝缘性质:聚酯亚胺/聚酰胺酰亚胺漆包线
公司地址	青浦区朱家角镇康业路901弄98号4层D区435室
联系电话	86 021 63526198/63525558 13501628398

产品详情

漆包线规格表
点击率：4660

铜芯标称直径(毫米)	漆包线最大外径(毫米)	铜芯截面积(平方毫米)	直流电阻(欧/千米)	漆包线重量(公斤/千米)	每厘米可绕圈数	近似的英规swg铜线 线号	铜芯直径(毫米)
0.03	0.045	0.0007065	24704	0.012	222.2	49	0.030
0.04	0.055	0.001257	13920	0.015	181.8	48	0.041
0.05	0.065	0.001963	8949	0.019	153.8	47	0.051
0.06	0.075	0.002827	6198	0.027	133.3	46	0.061
0.07	0.085	0.003848	4556	0.036	117.6	45	0.071
0.08	0.095	0.005027	3487	0.047	105.3	44	0.081
0.09	0.105	0.006362	2758	0.059	95.2	43	0.091
0.10	0.12	0.007854	2237	0.073	83.3	42	0.102
0.11	0.13	0.009498	1846	0.088	76.9	41	0.112
0.12	0.14	0.01131	1551	0.104	71.4	40	0.122
0.13	0.15	0.01327	1322	0.122	66.7	39	0.132

0.14	0.16	0.01539	1139	0.141	62.5		
0.15	0.17	0.01767	993	0.162	58.8	38	0.152
0.16	0.18	0.02011	872	0.184	55.6	37	0.173
0.17	0.19	0.02270	773	0.208	52.6		
0.18	0.20	0.02545	689	0.233	50.0	36	0.193
0.19	0.21	0.02835	618	0.259	47.6	35	0.213
0.20	0.225	0.03142	558	0.287	44.4	34	0.234
0.21	0.235	0.03464	506	0.316	42.6	33	0.254
0.23	0.255	0.04155	422	0.378	39.2	32	0.273
0.25	0.275	0.04909	357	0.446	36.4	31	0.295
0.27	0.31	0.05726	306	0.522	32.3	30	0.315
0.29	0.33	0.06605	265	0.601	30.3		
0.31	0.35	0.07548	232	0.689	28.6	29	0.345
0.33	0.37	0.08553	205	0.780	27.0	28	0.376
0.35	0.39	0.09621	182	0.876	25.6	27	0.417
0.38	0.42	0.11134	155	1.03	23.8	26	0.457
0.41	0.45	0.1320	133	1.20	22.2		
0.44	0.49	0.1521	115	1.38	20.4	25	0.508
0.47	0.52	0.1735	101	1.57	19.2	24	0.559
0.49	0.54	0.1886	89.0	1.71	18.5		
0.51	0.56	0.2043	85.9	1.86	17.9	23	0.610
0.53	0.58	0.2206	79.5	2.00	17.2		
0.55	0.60	0.2376	73.7	2.16	16.7		
0.57	0.62	0.2552	68.7	2.30	16.1	22	0.711
0.59	0.64	0.2734	64.1	2.48	15.6		
0.62	0.67	0.3019	58.0	2.73	14.9	21	0.813

0.64	0.69	0.3217	54.5	2.91	14.5		
0.67	0.72	0.3526	49.7	3.19	13.9	20	0.914
0.69	0.74	0.3739	46.9	3.38	13.5		
0.72	0.78	0.4072	43.0	3.67	12.8	19	1.016
0.74	0.80	0.4301	40.7	3.90	12.5		
0.77	0.83	0.4657	37.6	4.21	12.0		
0.80	0.86	0.5027	34.8	4.55	11.6	18	1.219
0.83	0.89	0.5411	32.4	4.89	11.2		
0.86	0.92	0.5809	30.1	5.25	10.9	17	1.422
0.90	0.96	0.6362	27.5	5.74	10.4		
0.93	0.99	0.6793	25.8	6.13	10.1		
0.96	1.02	0.7238	24.2	6.53	9.8	16	1.626
1.00	1.07	0.7854	22.4	7.10	9.4		
1.04	1.12	0.8495	20.6	7.64	8.9	15	1.895
1.08	1.16	0.9161	19.1	8.27	8.6		
1.12	1.20	0.9852	17.8	8.86	8.3	14	2.032
1.16	1.24	1.057	16.6	9.53	8.1	13	2.337
1.20	1.28	1.131	15.5	10.2	7.8		
1.25	1.33	1.227	14.3	11.1	7.5		
1.30	1.38	1.327	13.2	11.9	7.2		
1.35	1.43	1.431	12.3	12.9	7.0		
1.40	1.48	1.539	11.3	13.9	6.8		
1.45	1.53	1.651	10.6	14.9	6.5		
1.50	1.58	1.767	9.93	15.9	6.3		
1.56	1.64	1.911	9.17	17.2	6.1		
1.62	1.71	2.061	8.50	18.5	5.8		

1.68	1.77	2.217	7.91	19.9	5.6				
1.74	1.83	2.378	7.37	21.4	5.5				
1.81	1.90	2.573	6.81	23.1	5.3				
1.88	1.97	2.776	6.31	24.9	5.1				
1.95	2.04	2.987	5.87	26.8	4.9				
2.02	2.12	3.205	5.47	28.9	4.7				
2.10	2.20	3.464	5.06	31.1	4.5				
2.26	2.36	4.012	4.37	36.2	4.2				
2.44	2.54	4.676	3.75	42.2	3.9				

本产品的型号是QZQAQZY，绝缘性质为聚酯亚胺/聚酰胺酰亚胺漆包