

# ISP-A1C日本北阳hokuyo光资料传输装置

产品名称	ISP-A1C日本北阳hokuyo光资料传输装置
公司名称	杭州邦硕电子有限公司
价格	18000.00/个
规格参数	加工定制:否 品牌:北阳hokuyo 型号:isp-a1c
公司地址	拱墅区登云路639号(杭州电子市场二楼2A096号)
联系电话	0571-89902096

## 产品详情

this device can convert serial data into parallel output or parallel input into serial data. this device can transmit so many i/o signals with a few signal line. this device is much higher speed than usual type.

featureit can transmit signals with 16 points max./unit for both input and output.it can extend up to 128 points max. by increasing units.it can make a high-speed transmission with 62.5kbps.it can make a din-rail mounting with 35mm pitch.specifications

model no.

isp-a1c\*(main and sub)

power source

18 to 30vdc(ripple10%)

current consumption

input 85ma or less, output

serial interface

type

rs-422 and rs-485

	transmission method	full-duplex two-way tra
	transmission speed	62.5k/19.2k/9,600/4,800
	transmission distance	host communication: 50
parallel interface	input signal numbers	16 points(it can extend
	input circuit	photo-coupler isolation current: 5ma/1 point, 85
	output signal numbers	16 points(it can extend
	output circuit	photo-coupler isolation current: 50ma/1 point, 85
ambient temperature/humidity		-10 to +50 degrees c, 85
connection		screw terminal for power
case		abs resin(body), polycarbonate

weight

approx. 260g

\* use this device with bwf series. if cwf series, use isp-a1c-c.

external dimension

input/output circuit

parallel input

parallel output

+v is supplied from +24v. 0v is common use for power terminal 0v.

+v is supplied from +24v. 0v is common use for power terminal 0v.

serial input/output

warning output

connection

parallel input

parallel output

\*ask us about details specifications.

本产品的 是否提供加工定制为 否，品牌是 北阳hokuyo，型号为 ISP-A1C，结构类型是 放大器内藏型，