

24V 30Ah Lifepo4 リチウム電池バッテリー 電動自転車用可能

| | |
|------|--|
| 产品名称 | 24V 30Ah Lifepo4 リチウム電池バッテリー 電動自転車用可能 |
| 公司名称 | 上海雷瞬实业有限公司 |
| 价格 | 1946.00/个 |
| 规格参数 | 加工定制:是 品牌:conhismotor 型号:24v30ah |
| 公司地址 | 上海市闵行区中春路7001号2幢3楼A3004室 |
| 联系电话 | 86 021 64782671 18616508735 |

产品详情

上海雷瞬实业有限公司成立于二零一零年六月十三日,公司主营diy电动自行车改装套件、配套电动自行车电机及控制器等相关产品、高端自行车(路虎、宝马)改装、电动车配套(lifepo4)磷酸铁锂电池(银鱼系列、小青蛙系列、水壶式系列、以及大功率定制磷酸铁锂电池)、汽车剪刀门及氙气灯、碳纤维自行车整车、碳纤维轮组、配套花鼓、快拆、辐条、辐条帽、碳纤维轮圈等相关产品;公司产品90%出口到香港、台湾、日本、新加坡、澳洲、俄罗斯、乌克兰、欧洲、北美、南美、中东等。

上海雷瞬实业有限公司实力雄厚,重信用、守合同、保证产品质量,品种齐全、价格合理,以多品种经营特色和薄利多销的原则,赢得了广大客户的信任。

电池事业部拥有成熟的技术装配团队;一直以质量为基础,诚信为根本,长期为国内外客户提供优质产品;我们的电池主要用于电动车改装配套,家用储能,太阳能配套,电动汽车、电动摩托车等使用;电池事业部主要生产:水壶式电池、小青蛙式电池、银鱼系列电池、以及大功率筒包电池等产品。

24v 30ah lifepo4 battery (with bms,fast charger and bag):

brand new, a grade!!!

free charger, free bms, free battery bag!!!

24v 30ah lifepo4 battery specification:

| | |
|--|--|
| battery model | 24v 30ah |
| nominal capacity (ah) | 30ah |
| nominal voltage (v) | 25.6 |
| source resistance (mΩ) | < 40 |
| cell combination | 8-series11-parallel |
| cell type | 26650 cylindrical(3.2v 30ah) |
| cell quantity (series*parallels) | 88 pcs |
| cell size | diameter: 26mmheight: 65mm |
| batterysize | 310 × 210 × 75mm 310 × 120 × 120mm |
| discharge cutoff voltage (v) | 17.6 |
| charge cutoff voltage (v) | 31.2 |
| rated discharge current (a) | 30 |
| instantaneous maximum discharge current(a) | 60 |
| maximum continuous discharge current(a) | 60 |
| maximum continuous charge current(a) | 15 |
| maximum standard bms limited current (a) | 30if you have special requirement, please contact us |
| charge mode | cc-cv |
| standard charge current (a) | 2 |
| charge time under standard chargecurrent | 18 hours |
| fast charge current (a) | 6 |
| charge time under fast chargecurrent | 6 hours |
| charge temperature range | 0-45 |
| discharge temperature range | -10-60 |
| battery net weight (include bms) (kg) | 7.5 |
| battery gross weight (include bms) (kg) | 11 |
| lasting distance (24v 500w motor) | 44km |
| charging cycles | >1000 times |
| equipment | bms + 6a fast charger |
| recommend motor application | 24v 200w, 24v 250w, 24v 350w |

| | safety | cycle life | power weight density | long term cost | temperature range |
|------------|---|---|----------------------|-------------------------|---|
| lifepo4 | excellentsafest and most envirofriendly among all the listedgroups | excellent cycle life can be as long as over 2,000 cycle, best amongall the listed groups. | acceptable | excellentm ost economic | excellent (can be discharged at -45~ 70 centigrade) |
| licoo2 | very unstable, must handle with extremely care, it might explode orcatch fire under collision, over-charged, short circuit or when heat build-up. | acceptable cycle life only up to 300~500 cycle. not good for highc-rate discharge. | good | high > | decayed beyond 55 ~ -20 centigrade |
| limn2o4 | have to handle with care, or it might explode or catch fire undercollision or over-charged. | unacceptable cycle life only up to100~800 cycle, depending on thedischarge c-rate. | acceptable | acceptable | high |
| li(nico)o2 | very unstable, must handle with extremely care, it might explode orcatch fire under collision, over-charged, short circuit or when heat build-up. | acceptable cycle life can be 300~500 cycle. not good for high c-ratedischarge. | good | high | decayed extremely fast over 55~ -20 centigrade |

本产品的 加工定制为 是 ， 品牌是 conhismotor ， 型号为 24V30Ah ， 标准电压是 24V ， 额定容量为 30Ah ， 产品认证是 CE ，