

GDM系列 HIRSCHMANN 德国赫斯曼接头连接器

产品名称	GDM系列 HIRSCHMANN 德国赫斯曼接头连接器
公司名称	南京希川自动化设备有限公司
价格	16.00/个
规格参数	加工定制:否 品牌:hirschmann德国赫斯曼 型号:gdm系列
公司地址	南京市浦口区大桥北路9号016幢旭日华庭金棕榈 弘阳大厦1单元1913室
联系电话	025-58607989 18751808105

产品详情

hydraulic, pneumatic and electromagnetic actuators and sensors – where hardness meets hardness, the gdm-series is fully within its element. and for this reason, the rectangular connector with a high loading capacity is especially well-suited for use with solenoid valves, pressure sensors, flow controllers and in heating equipment in control systems for gas appliances and oil burners. even in vibration-endangered devices and structural components such as construction machines or in conveyor installations, it is possible to have a highly durable solution with the use of crimp technology.with built-in electronic components such as rectifiers, optical status displays and protective elements, the gdm-series can be connected to devices where these functions have not been integrated. and last but not least, the gdm-series can be used wherever a “ metal-free ” environment is required, for example in the food sector and the chemical industry.the gdm-series is used wherever rectangular connectors have to have resilient qualities, such as for example on drilling rigs, conveyor installations or in construction machines.the rectangular connector with a large range of cable diameters from 4.5mm to 14 mm is protected against dust and sprayed water with vibration-free locking with a central screw; a knurled screw can also be supplied for use without tools. the valve professional for pneumatic and hydraulic systems. durability tests successful: the gdm-series can outplug many others.

详细参数

2 + pe / 3 + pepg 9 / pg 11 / m 16max. 1.5 mm²din en 175 301-803-ablacka6.3 mm x 0.8 mm, 4.8 mm x 0.8 mmac/dc
250 v16 a 4 mohmscrew4.5 mm to 10 mm diametercentral nutip 65 (gasket necessary)-40 ° c to +125 ° c

南京希川自动化设备有限公司

地址：江苏省南京市浦口区大桥北路9号。

tel : 025-58607989

mob : 18751808105

fax : 025-58402959

qq : 2496603078

可以为您提供专业的工业自动化仪器仪表的服务与技术支持：德国 赫斯曼连接器 hirschmann gdm系列。

本产品的 额定电压为 AC/DC250V，接口类型是 DIN(大/中/小)，接触件材质为 CuZn(Sn)，额定电流是 16A，针数为 2+PE/3+PE，种类是 插头/插座，温度范围为 -40 ° C~+125 ° C，加工定制是否，形状为 矩形，线长是 客户指定 (mm)，应用范围为 传感器，型号是 GDM系列，工作频率为 低频，特性是 防水，品牌为 HIRSCHMANN德国赫斯曼，绝缘体材质是 PA，制作工艺为 注塑，芯数是 2+PE/3+PE，