

MOLY-TEC涂料Oxy-Lube E

产品名称	MOLY-TEC涂料Oxy-Lube E
公司名称	上海恩莱保贸易有限公司
价格	.00/件
规格参数	Oxy-Lu:Oxy-Lube E
公司地址	上海市松江区金高路2388号813室
联系电话	86-021-20228098 13391171050

产品详情

Oxy-Lube E is a dry-film lubricant qualified to D6-3488, BAC5811, AS6449 & AS6450. It is designed for use on Oxygen, Potable Water and Hydraulic Fittings. Oxy-Lube E has an exclusive pigment-to-volume ratio that allows it to provide exceptional anti-galling properties, while maintaining effective corrosion barrier protection.

This unique ratio also gives it a distinct advantage against leading dry-film lubricants since coating transfer is minimal. Oxy-Lube E operating temperature ranges from -90 F to 600 F (-67 C to 315 C).

Oxy-Lube E是一种符合D6-3488、BAC5811、AS6449和AS6450标准的干膜润滑剂。它是专为使用氧气，饮用水和液压配件。Oxy-Lube E具有独特的颜料与体积比，使其能够提供卓越的抗磨损性能，同时保持有效的腐蚀屏障保护。

这种独特的比例也使它具有明显的优势，相对于lingxian的干膜润滑剂，因为涂层转移是最小的。Oxy-Lube E工作温度范围为-90F至600F(-67C至315C)。