

## DP7000温度仪表与报警或开关控制和蜂鸣器发声

|      |                             |
|------|-----------------------------|
| 产品名称 | DP7000温度仪表与报警或开关控制和蜂鸣器发声    |
| 公司名称 | 合肥永准仪器仪表有限公司                |
| 价格   | 面议                          |
| 规格参数 |                             |
| 公司地址 | 合肥市瑶海区濉溪路与张洼路交口星海世纪广场B1504室 |
| 联系电话 | 0551-62782344 13855103484   |

### 产品详情

the dp7000 series temperature meters offer a wide temperature range, 2 selectable alarm settings, and an internal buzzer that indicates alarm condition or error. the user can define setpoint, on/off heating/cooling regulation, alarm configuration, load status, and ambient probe adjustment. other features include password protection and error/alarm messaging. temperature and output status is indicated on the bright-red led display. the dp7000 can be programmed for j or k thermocouple inputs. applications these meters are suitable for industrial chillers, environmental chambers, walk-ins and freezers, heat sealers, sterilizers, coolers, display cases and cabinets, warmers, meat and produce storage, floral preservation, laboratories, food service equipment, ovens and dryers, tool rooms, and burn-in rooms and chambers. specifications range: thermocouple j: 0 to 700 ° c (32 to 999 ° f) thermocouple k: 0 to 999 ° c (32 to 999 ° f) inputs: type j or k thermocouple output: 15 a spdt relay @ 250 vac resistive horsepower rating (hp): 3/4 control type: on/off power requirement: 110 vac, 230 vac, 12 vac/vdc or 24 vac/vdc (depending on model) power consumption: 4 va accuracy: ± 1% fs display: three 12.7 mm (1/2") red digits, plus sign display update rate: 16 seconds resolution: 1 ° memory backup: non-volatile memory operating temperature: -10 to 70 ° c (14 to 158 ° f) storage temperature: -20 to 80 ° c (-4 to 176 ° f) weight: 65 g (2.3 oz) front-panel rating: nema 4x (ip66)