

DP63000数字面板仪表，温度，电压和电流

产品名称	DP63000数字面板仪表，温度，电压和电流
公司名称	合肥永准仪器仪表有限公司
价格	面议
规格参数	
公司地址	合肥市瑶海区濉溪路与张洼路交口星海世纪广场B1504室
联系电话	0551-62782344 13855103484

产品详情

dp63000数字面板仪表，温度，电压和电流 the dp63000 series provides the user the ultimate in flexibility, from its complete user programming to the optional setpoint control and communication capability. the dp63000-tc accepts a thermocouple input. the dp63000-rtd accepts an rtd input and both provide a temperature display in celcius or fahrenheit. the meter also features minimum and maximum display capture, display offset, ° f or ° c indicator, and programmable user input. the display can be toggled either manually or automatically between the selected displays. other models include process, dc voltage or current input signal and provides a display in the desired unit of measure. the dp63000 series display has 12.2 mm (0.48") h digits. the lcd model is available in 2 versions, reflective and red/green backlight. the backlight version is userselectable for the desired color and also has variable display intensity. the capability of the dp63000 can be easily expanded with the addition of option modules. setpoint capability is field-installable with the addition of the setpoint output modules. serial communications capability for rs232 or rs485 is added with a serial option module. the dp63000 can be powered from an optional power supply that attaches directly to the back of a dp63000. the power supply is powered from 85 to 250 vac and provides up to 400 ma to drive the unit and sensors. to order what other people bought: when you see this icon, click on it to expand a list of products that other people have bought when they purchased this model. part number availability price description qty. dp63000a-t thermocouple input, reflective display, 9 to 28 vdc dp63000b-t 1 week thermocouple input, backlight display, 9 to 28 vdc dp63000a-rtd 5 weeks rtd input, reflective display, 9 to 28 vdc dp63000b-rtd 1 week rtd input, backlight display, 9 to 28 vdc dp63000a-e 5 weeks process input, reflective display, 9 to 28 vdc dp63000b-e 5 weeks process input, backlight display, 9 to 28 vdc dp63000a-v 5 weeks dc volt input, reflective display, 9 to 28 vdc dp63000b-v dc volt input, backlight display, 9 to 28 vdc dp63000a-i 4 weeks dc current input, reflective display, 9 to 28 vdc dp63000b-i 1 week dc current input, backlight display, 9 to 28 vdc optional plug-in output cards (field installable) setpoint alarms (only 1 alarm card can be installed into base meter) dp6-rly0 2 weeks \$40.00 single relay output card dp6-snk0 2 weeks \$20.00 dual sinking output card communications (only 1 communications card can be installed into base meter)* dp6-com1 rs485 serial communications output card dp6-com2 1 week rs232 serial communications output card accessories (field installable) dp6-mlps1 1 week micro-line power supply, 85 to 250 vac dp6-232-cable rs232

programming cable (db9-rj11) dp6-485-cable rs485 programming cable (db9-rj11)