

ADA Rotating Hoist Ring UNC, Grade 8 rotating ring

产品名称	ADA Rotating Hoist Ring UNC, Grade 8 rotating ring
公司名称	川尚机械设备（武汉）有限公司
价格	1000.00/件
规格参数	ADA:3/8 ADA:3/4 ADA:1 1/2
公司地址	武汉经济技术开发区12C2地块武汉经开万达广场B区S53栋30层B315室(商务秘书WYLM252)
联系电话	18674085456 18674085456

产品详情

ADA Rotating Hoist Ring UNC, Grade 8 rotating ring

ADA Rotating Hoist Ring UNC GR8

Product code: ADAUNC

Material: alloy steel, Grade 8, quenched and tempered

Safety Factor: MBL equals 5 x WLL

Finish: painted white

Temperature range: -40度 up to +200度 (-40度 up to +392度)

Certification:CE

Note: WLL indicated hereunder are given in the worst

conditions of use, i.e. 90度

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 5/16", WLL 0.4 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 3/8", WLL 0.6 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 1/2", WLL 1 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 5/8", WLL 1.7t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 3/4", WLL 2.5 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 7/8", WLL 3.5 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 1", WLL 4.5 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 1 1/4", WLL 6.8 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 1 1/2", WLL 10.8 t

ADA Rotating Hoist Ring UNC, Grade 8 rotating hoist ring UNC, painted white, diameter thread 2", WLL 13.6 t

The Rotating Hoist Ring UNC range has been expanded with three extra sizes from WLL 6.8t up to 13.6t.

The Rotating Hoist Ring UNC is a grade 8 rotating hoist ring with UNC thread. This hoist ring with UNC thread can

pivot 180度 and rotate 360度. It has UNC threads as standard. The cylindric head of the screw prevents jamming during rotation of the shackle.

The WLL indicated hereunder are given in the worst conditions of use, i.e. 90度. It is necessary to check the free moving of the pivoting shackle. WLL and CE marking are mentioned on the product. The minimum safety factor is 5:1.

Rotating Hoist Ring UNC is available in a range with a working load limit from 0.4t up to 13.6t.

Additional information on the hoist rings are available on the tel