

替代RL895-471K-RC 470UH铜铁共烧贴片插件工字大电流功率AI人工智能TLVR笔记本主板电感

产品名称	替代RL895-471K-RC 470UH铜铁共烧贴片插件工字大电流功率AI人工智能TLVR笔记本主板电感
公司名称	深圳市好东方新能源环保有限公司
价格	1.30/件
规格参数	品牌:H-EAST/好东方 封装/规格:DIP/RL895 型号:RL895-471K-RC 470uh
公司地址	深圳市宝安区沙井街道新和路衙边第三工业区
联系电话	18319053074 18319053074

产品详情

H-EAST好东方替代Bourns电感	电感值(μ H)	DCR Typ(m	饱和电流) (A)	温升电流 (A)	工作温度()	长(mm	宽(mm	高(mm	封装
RL895-100M-RC	10	27.8	5.6	4.08	-40~125	8.3	8.3	10	DIP
RL895-101K-RC	100	192	1.82	1.57	-40~125	8.3	8.3	10	DIP
RL895-102K-RC	1000	1820	0.59	0.47	-40~125	8.3	8.3	10	DIP
RL895-103K-RC	10000	18937	0.17	0.14	-40~125	8.3	8.3	10	DIP
RL895-121K-RC	120	222	1.5	1.42	-40~125	8.3	8.3	10	DIP
RL895-122K-RC	1200	2073	0.49	0.44	-40~125	8.3	8.3	10	DIP
RL895-150M-RC	15	38	4.7	3.63	-40~125	8.3	8.3	10	DIP
RL895-151K-RC	150	285	1.4	1.31	-40~125	8.3	8.3	10	DIP
RL895-152K-RC	1500	2643	0.45	0.4	-40~125	8.3	8.3	10	DIP
RL895-180K-RC	18	42	4.3	3.43	-40~125	8.3	8.3	10	DIP
RL895-181K-RC	180	329	1.23	1.18	-40~125	8.3	8.3	10	DIP
RL895-220K-RC	22	46.2	3.8	3.28	-40~125	8.3	8.3	10	DIP
RL895-221K-RC	220	370	1.2	1.12	-40~125	8.3	8.3	10	DIP
RL895-222K-RC	2200	4006	0.39	0.32	-40~125	8.3	8.3	10	DIP
RL895-223K-RC	22000	44300	0.15	0.09	-40~125	8.3	8.3	10	DIP
RL895-330K-RC	33	60	3.3	2.88	-40~125	8.3	8.3	10	DIP
RL895-331K-RC	330	572	1.02	0.84	-40~125	8.3	8.3	10	DIP
RL895-332K-RC	3300	6273	0.32	0.25	-40~125	8.3	8.3	10	DIP
RL895-363K-RC	36000	71865	0.1	0.08	-40~125	8.3	8.3	10	DIP
RL895-392K-RC	3900	7107	0.3	0.24	-40~125	8.3	8.3	10	DIP
RL895-470K-RC	47	87.2	2.75	2.35	-40~125	8.3	8.3	10	DIP
RL895-471K-RC	470	870	0.85	0.69	-40~125	8.3	8.3	10	DIP

