

美孚Greasrex K-218高温润滑脂

产品名称	美孚Greasrex K-218高温润滑脂
公司名称	深圳市鑫隆达润滑油有限公司
价格	720.00/桶
规格参数	品牌:美孚 规格:16KG 服务范围:全国
公司地址	深圳市龙华区龙华街道富康社区东环二路61号颖博办公楼2层A2002
联系电话	15361061508 15817364911

产品详情

美孚Greasrex K-218

Grease

Product Description

Greasrex K-218 is an NLGI grade 2 product designed for the post tension construction industry. It has controlled oil bleed to prevent oil separation on tendon manufacture. It has exceptional corrosion protection and salt water resistant properties for corrosion prevention over the life of the finished structure. It is compatible with the polymers used for sheathing the post tensioning tendons. Greasrex K-218 contains a high quality ISO VG 100 mineral base oil and a lithium hydroxystearate / polymer thickener.

Features and Benefits

Greasrex K-218 offers the following features:

High quality base grease with good stability and low oil separation tendency

Uses high quality base oil and thickener components

Manufactured to high standards of quality and consistency between batches in modern manufacturing facilities
Applications

Base grease for third party blenders for use in a variety of finished products

Concrete post tensioning cable coating

Typical Properties

Greasrex K-218	
NLGI Grade	2
Thickener Type	Lithium/Polymer
Color, Visual	Light Brown
Penetration, Worked, 25 C, ASTM D 217	280
Dropping Point, C, ASTM D 2265	188
Viscosity of Oil, ASTM D 445	
cSt @ 40 C	100
Roll Stability, ASTM D 1831, mm/10	4.5
Oil Separation, ASTM D 6184 30 hrs at 71 C	0.07