

1 × 8机械式光开关

产品名称	1 × 8机械式光开关
公司名称	珠海飞宇光电科技有限公司
价格	面议
规格参数	
公司地址	珠海市香洲人民东路81号二层东9号
联系电话	0755-85250091-2816 13926501293

产品详情

specifications

parameters	fy-1 × n		
insertion loss db	1<n 45 typ:0.8 max:1.0	45<n 88 typ:1.2 max:1.5	88<n 128 typ:1.7 max:2.0
wavelength range nm	850 ± 40/1300 ± 40 850 (sm)	1260~1650 1260~1620 (sm)	
test wavelength nm	850/1310 850	1310/1550 1310/1490/1550/1625	
return loss db	sm 50、 mm 30		
crosstalk db	sm 55、 mm 35		
pdl db	0.05		
wdl db	0.25		

db							
tdl	db					0.25	
repeatability	db					± 0.05	
durability	cycles					10 million	
transmission power	mw					500	
switch time	ms					10(sequence switch time of adjacent channel)	
operating temperature	° c					-20 ~ +70	
storage temperature	° c					-40 ~ +85	
power supply	v					+5 or 12	
relative humidity						5 ~ +95	
dimension	mm	1<n<4 (135 × 40 × 32)	4	n	12 (135 × 64 × 32)	12<n	16(184 × 78 × 36)
		16<n	45(184 × 78 × 66)	n	<88 (184 × 156 × 66)	88	n 128(184 × 220 × 66)
		n	16(140 × 77.5 × 32)	n	32(140 × 77.5 × 64)		

ordering information

channel	mode	wavelength	voltage type	fiber type	fiber diameter	fiber length	connector
---------	------	------------	--------------	------------	----------------	--------------	-----------

1~128	s=sm m=mm	85=850nm	3=5v	5=50/125	25=250um	05=0.5m	0=none
		13=1310nm	5=12v	6=62.5/125	90=900um;	10=1.0m	1=fc/pc
		15=1550nm		9=9/125	20=2.0mm	15=1.5m	2=fc/apc
		162= 1625nm		x= other	30=3.0mm	x=other	3=sc/pc
		165=1650nm			x= other		4=sc/apc
		13/15=1310/1550nm					5=st/pc
							6=st/apc
					7=lc/pc		
					8=lc/apc		
					x=others		