

Mobil fluid LT变速箱油

产品名称	Mobil fluid LT变速箱油
公司名称	深圳市鑫隆达润滑油有限公司
价格	650.00/桶
规格参数	品牌:美孚 规格:18L 服务范围:全国
公司地址	深圳市龙华区龙华街道富康社区东环二路61号颖博办公楼2层A2002
联系电话	15361061508 15817364911

产品详情

Mobilfluid LT

Mobilfluid LT

Extra High Performance Multipurpose Tractor Fluid

Product Description

Mobilfluid LT is an extra high performance multipurpose tractor lubricant engineered to meet or exceed tractor transmission, drivetrain, and hydraulic fluid requirements. This product is designed to optimize the performance of agricultural and industrial tractors operating in a wide range of environments and especially in low ambient temperature applications. This next generation product combines select base oils and an advanced additive package to deliver a variety of lubricant performance properties required by various applications.

Features and Benefits

Next generation technology has vastly improved the performance capabilities of heavy-duty equipment in terms of load, speed, control, and reliability through innovative drivetrain designs. These designs have changed and increased the requirements of drivetrain fluids to deliver higher levels of performance and productivity while reducing operating costs. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and pumpability are features that must be optimally balanced to provide extended clutch life, maximum drawbar loading, and maintain operations on uneven terrain over a wide range of ambient temperatures. Mobilfluid LT delivers

exceptional performance in today's drivetrain transmissions, drive axles, clutches, Power Take-Offs (PTO) and hydraulic systems and especially in low ambient temperature conditions. The key

Applications

Recommended by ExxonMobil for use in:

Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs, and hydrostatic drives used in agricultural, contractor, and industrial applications

Recommended for top-up and refill of systems

Suitable for transmission applications requiring Type A (Suffix A), Dexron, and Type F fluids

Recommended for hydraulic and transmission systems where an SAE 10W-20 engine oil is specified

Do not use in passenger car automatic transmissions

Typical Properties

Mobilfluid LT	
SAE Grade	75W-80
Viscosity, ASTM D 445	
cSt @ 40C	34
cSt @ 100C	7.2
Brookfield Viscosity, cP (@ -40C)	20,000
Viscosity Index, ASTM D 2270	180
Pour Point, C, ASTM D 97	-45
Flash Point, C, ASTM D 92	198
Density @ 15C kg/l, ASTM D 4052	0.875