

Mobilube HD Plus 85W-140车用齿轮油208L

产品名称	Mobilube HD Plus 85W-140车用齿轮油208L
公司名称	深圳市鑫隆达润滑油有限公司
价格	4500.00/桶
规格参数	品牌:美孚 规格:208L 服务范围:全国
公司地址	深圳市龙华区龙华街道富康社区东环二路61号颖博办公楼2层A2002
联系电话	15361061508 15817364911

产品详情

Mobilube HD Plus 85W-140

Mobilube HD Plus 80W-140

Mobilube HD Plus 80W-90

Mobilube HD Plus 80W-90, 85W-140

Extra High Performance Commercial Gear Lubricants

Product Description

Mobilube HD Plus 80W-90 and 85W-140 are extra high performance commercial gear lubricants formulated from select base oils and an advanced additive system. These lubricants are engineered for performance in heavy-duty commercial transmissions, axles, and final drives where extreme pressures and shock loading are expected. They provide excellent chemical and thermal stability at elevated bulk oil temperatures, good performance at low temperatures, and have demonstrated good rust protection resulting from water contamination and wet conditions. They are recommended by ExxonMobil for applications where API GL-5 and MT-1 service is required. Mobilube HD Plus 80W-90 and 85W-140 share common formulations with Esso Gear Oil GX 80W-90 and 85W-140.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant. Mobilube HD Plus gear lubricants are engineered to meet these challenges. The key benefits include:

Recommended by ExxonMobil for use in:

Heavy-duty manual transmissions, axles, and final drives requiring API GL-5 and MT-1 level performance

On-highway light and heavy-duty trucks, busses, vans, and cars

Off-highway industries including: construction, mining, quarrying, and agriculture

Other heavy-duty industrial and automotive applications involving hypoid and other gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque conditions prevail

Initial fill, top-off, and refill of enclosed commercial gearing in manual or semiautomatic transmissions where gear lubricants are recommended including drive axles and final drives

Not recommended for applications requiring API GL-4 Level performance

Not intended for transmissions for which engine oil or automatic transmission fluids are recommended

Typical Properties

Mobilube HD Plus	80W-90	85W-140
SAE Grade	80W-90	85W-140
Viscosity, ASTM D 445		
cSt @ 40C	139	333
cSt @ 100C	14.5	25.4
Viscosity Index, ASTM D 2270	103	99
Pour Point, C, ASTM D 97	-27	-18
Flash Point, C, ASTM D 92	210	230
Density @ 15C kg/l, ASTM D 4052	0.895	0.903