

CSB蓄电池GP12120 F2 12V12AH用电梯 船舶 应急电源 UPS储能

产品名称	CSB蓄电池GP12120 F2 12V12AH用电梯 船舶 应急电源 UPS储能
公司名称	山东德力特电源科技有限公司
价格	.00/件
规格参数	品牌:CSB蓄电池 型号:GP12120 F2 产地:台湾
公司地址	北京昌平区回龙观
联系电话	15911127756 15911127756

产品详情

Powered by

GP series

GP 12120 12v12AH

Valve Regulated lead Acid Battery

Maintenance-Free Sealed lead Acid Battery. Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99%

Design for Standby Power Applications

【Design Life】

Up to 5 Years in Standby Service at 25°C

Robot (20') : 3-5 years, Standard Commercial

【Operating Temperature Range】 Nominal Operating Temperature : 25°C (77°F)

Discharge: -15 ~ 50 (5°F ~ 122°F)

Charge: -15 ~ 40 (5°F ~ 104°F) Storage: -15 ~ 40 (5°F ~ 104°F)

【Float Charging Voltage】 13.5~13.8 VDC/nit at 25°C (77°F) 【Equalization charging Voltage

14.4~15.0VDC/Unt at 25 (77F) Self Discharge】

Less than 10% after 90 days, can be stored up to 6 months at 25 (77 F), Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25 C (77F)

Specification

Design according with IEC 61056-1/2: 2012

Nominal Voltage

Nominal Capacity

Weight

Maximum Discharge Current

internal Resistance

Short Circuit Current

Maximum Charge Current

Terminal types

Terminal hardware Torque

Container Material

Dimensions

12V (6 cells per unit)

12Ah @20hr-rate to 1.75V per cell @25 (77°F)

Approx. 3.67 Kg (8.09 lb)

150/180A (5sec)

Approx. 16.7mm

378A

3.60A

F1/F2 terminal - faston Tab 187/250

ABS (UL 94-HB) & Flame Retardant (94-V) available upon request

5.94±0.08 inch

Length (L)

151.0+2.0 mm

Wdth (w

98.0+1.0 mm

3.86+0.04 inch

Container Height (h)

94.1+1.0 mm

3.70+0.04 inch

1传用华H0

重量有多少?

Overall Height (H)

100.3 ± 1.5 mm

3.95+0.06 inch

Constant current Discharee characteristics Unit: A(2596.779=

60MN

F.V/Time

SMIN

101A

25办内1

30 N

C0NI

2H

3周东

SHR

23 9

1.60V

13.9

5.90

4.65

2.24

4.6

222

1.67V

92

1.70V

6

3

2.18

1.75V

5.77

4.57

112

1.85V

44.29

5.41

32

25.3

19.8

123

7.51

3.03

197

C0nSAntP0

roischareecharacteristics Unit:w(25..77

FV/Time

SNIN

15CMIN

60MVIN

1011

301

90IIN

2HR

3HR

5HR

爬管

1.60V

539

97.9

55.9

39.6

160

70.6

70.2

1.67V

342

265

159

97.7

55.6

39.3

e

33

262

25.0

1.70

158

97.0

69.9

55

39

10

°

1 85V

91 6

52.6

36.3

23年

66.2

Please refer to the official site for the latest rating confirmation, URL: www.csb-battery.com

8HR

.4

1.40

1.32

8HR

16.7

16.6

16.

15

15.5

10HR

1.19

115

1.09

10HR

13.8

13.7

1

12.

15sued:

20HR

0.63

0.6.

0.63

0.60

0.57

20HR

1.70

7.63

7.61

161101

