

GYTC8A(GYTC8S)自承式松套管层绞式8字光缆

产品名称	GYTC8A(GYTC8S)自承式松套管层绞式8字光缆
公司名称	安徽飞讯通信设备有限公司
价格	.00/件
规格参数	
公司地址	安徽省阜阳市临泉县邢塘街道办事处霞光大道16号安徽柏联创新科技产业园17号楼1楼
联系电话	0558-8538890 18855856323

产品详情

GYTC8A 光缆的结构是将 250m 光纤套入高模量材料制成的松套管中，松套管内填充防水化合物。缆芯的中心是一根金属加强芯，松套管（和填充绳）围绕中心加强芯绞合成紧凑和圆形的缆芯。缆芯用一层涂塑铝带（APL）纵包后，和钢丝绞线集成到一个 8 字型的聚乙烯护套内。可提供 Y 护套或 S 护套的 8 字型光缆 GYTC8Y、GYTC8S 等，此类产品多应用于自承式架空敷设。

具有很好的机械性能和温度特性 Excellent mechanical and temperature performance

松套管材料本身具有良好的耐水解性能和较高的强度 Special tube filling compound ensure a critical protection of fiber and resist the water.

单根钢丝作为纵向中心强度构件 Single steel wire as the central strength member to withstand axial loads.

PE护套具有良好的抗紫外线功能 PE sheath protects cable from ultraviolet radiation.

完全缆芯填充 100% core filling water prevent cable jelly to ensure the cable watertight.

铝带（或钢带）纵向覆盖电缆芯作为防潮层 APL(or PSP) longitudinal cover cable core as moisture barrier.

钢丝绞线具有极高的抗拉强度，便于自承式架空敷设，降低安装成本 High tensile strength of stranded wires meet the requirement of self-supporting and reduce the installation.