

# APCSmart-UPSRT5000VA230VUPS不间断电源SURT5000XLICH/5KVA

产品名称	APCSmart-UPSRT5000VA230VUPS不间断电源SURT5000XLICH/5KVA
公司名称	北京狮克电源科技有限公司
价格	9900.00/台
规格参数	品牌:APC 是否支持加工定制:是 安装方式:机架式/塔式互换
公司地址	北京市昌平区顺沙路88号
联系电话	010-56018769 18612657778

## 产品详情

APCSmart-UPSRT5000VA230VUPS不间断电源SURT5000XLICH/5KVA

品牌

APC

是否支持加工定制

是

是否进口

是

安装方式

机架式/塔式互换

包装清单

标准配置

备用时间

0.5h

标称容量

5000VAW

产品认证

ce

电源名称

UPS不间断电源

调制方式

脉冲频率调制(PFM)式

晶体管连接方式

单端式

输出电压

230VDCV

输出功率

3500WW

输入电压

230VACV

数量

600

可售卖地

全国

类型

AC/DC电源

型号

SURT5000XLICH

Smart-UPS On-Line 性能与优势

可用性

## 自动内部旁路

在UPS电源出现过载或故障的情况下向所连接的负载提供公用电源。

## 可扩展的运行时间

需要时允许快速增加更多的运行时间

## 智能电池管理

通过智能、精确的充电技术获得电池性能、寿命和可靠性。

## 热插拔电池

在更换电池的整个过程中，确保干净、不间断电源以保护设备

## 经 UPS 关机后自动重启负载

一旦市电恢复，则自动重新启动所连接的设备。

## 温度补偿电池充电

根据实际的电池温度调整充电电压延长电池寿命

APC Smart-UPS RT 5000VA 230V UPS不间断电源APC SURT5000XLICH 5KVA

### Overview

Lead time

Usually in Stock

### General

provided equipment

CD with softwareSmart UPS signalling RS-232 cableUser manualWeb/SNMP management

performance multiplier

1

Number of tare power

Number of power module free slots

Number of

power module filled slots

0

redundant

No

size UPS version

InternetworkingServerTe

UPS size

value multiplier

### Physical

number of rack unit

3U

colour

Black

depth

69.85 cm

height

43.2 cm

mounting location  
mounting preference  
net weight  
mounting mode  
two post  
mountable  
0  
USB compatible  
No  
width  
13 cm  
Input  
network frequency  
50/60 Hz +/- 5 Hz auto-sensing  
number of input connectors  
1 hard wire 3-wire  
input voltage limits  
280 V ac  
inputvolt\_other  
input voltage  
Output  
rated power in W  
3500 W  
Maximum configurable power in W  
3500 W  
harmonic distortion  
output frequency  
outputvolt\_other  
crest  
factor  
3 : 1  
UPS type  
Double conversion online  
Wave type  
Sine wave  
nb of power socket outlets  
8 IEC 60320 C134 IEC Jumpers2  
bypass type  
Internal bypass (a  
curve equation  
curve load maximum  
curve X-axis  
maximum  
curve X-axis minimum  
0 %  
curve X-axis title  
Load  
curve X-axis units  
curve Y-axis maximum  
curve Y-axis minimum  
curve Y-axis title  
Efficiency  
curve Y-axis units  
Percentage  
efficiency  
92 % (full load)  
graph display  
1  
output voltage  
Maximum configurable power in VA  
rated  
power in VA  
5000 VA  
Conformance

product certifications

C-TickCEGOSTVDE

standards

EN 50091-1EN 50091-2EN 55022 class AEN 60950EN 61000-3

Environmental

ambient air temperature for operation

0...40 ° C

relative humidity

0...95 % non-conden

operating altitude

ambient air temperature for storage

storage

altitude

0.00...15240.00 m

acoustic level

55 dBA

heat dissipation

1057 Btu/h

show note OP temperature

IP degree of protection

Batteries & Runtime

battery type

Lead-acid battery

number of battery filled slots

2

Battery recharge time

2.5

number of battery replacement quantity

additional

information

Configurable for 220 : 230 or 240 nominal output voltage

liquid value

0

battery curve

C

battery charger power

382 W rat

Battery power in VAH

battery life

battery option

SURT192

VAhSURT192X

extended

runtime

1