ABB无火花电机

产品名称	ABB无火花电机	
公司名称	无锡鸿良自动化设备有限公司	
价格	1000.00/台	
规格参数	品牌:ABB	
公司地址	无锡市崇安区广瑞路780号名景区大厦1014室	
联系电话	0510-82447181	

产品详情

abb?? ??

http://www.wx-hl.com

http://www.xmzmotor.com

????

exna||t3-m2gp?????????2003?1?24??????

various kingds of flammable gases or vapor may possibly exist in coal, petrolerm and chemical industries, etc. during production. when these substances mix with air, they will form an explosive mixture.if the mixture reaches uts explosive limit and tinder is occurred, a serious explosion will certainly happen.therefore,ex na/eex na? t3-m2qp non-sparking motors are severely examined according to iec60079-15during the test. ex na/eex na ?t3-m2gp non-sparking motors have been approved by national quality supervison and inspection center of flameproof products, and achieved certificate of conformity, ex na/eex na application areas of ex na/eex na motors technical features high efficiency be up to the class 2 of cemer-eu standard and the efficiency of 3 phase small &medium induction motors of chinese standard gb18613-2002 dual frequency, wide voltage the range of voltage is 220v-690v*, 50hz and 60hz supplies applicable.

????????????

????	iec	60079-15
????	gb	3836.8
????	en	50021
????	ul	2279
?????	roct	p51330.14
????	bs	5000-16

exna???????

????????t3????????????200????????? -15?-40?? ????

???

????cemep-eu???????????????????? gb18613-2002???????????????

?????

????220v-690v???50hz?60hz??? ??? ????? ????????????m2qp?????????? ??????

??????????????80-225????????????25 0-355??????

????

????????y-????????

low noise the m2gp range has been designed to minimize motors noise levels, by means of improving magnetic and electrical design, ventilator condition, and structure assembling size and technology. bearings with high load capacity standard motors are provided with deep-groove ball bearings, the lifetime is extended motors in sizes 71-225 are greased for life, and those in sizes 250-355 have a regreasing device as a standard, high reliability motor are to totally enclosed fan coolde ip55.materials and procedures satisfy with environmental requirements.the motor is mechanically strong and corrosion resistant.windings have a good reliability in class f insulation, and class b inspection.ptc thermistors or therm-swithches are available on request. the rated voltage of frame size h100 and below is 220v-480v, see ex certificate table (page 9) working conditions ambient temperature:to be altered with the change of seasons, but do not exceed -40?~+40?* altitude:to be used lower than 1,000 meters above sea level. rated frequency: 50hz/60hz rated voltage: 220v~690v duty:continuous(s1) method of starting:can be started on full voltage motors and can be started with y- starter or reactor. driving method: flexible couping or spur gear can be used for driving, insulation and temperature rise: class f.but the temp.rise of the stator windings is limited at 80k,i.e.treated as class b(resistance method).permissible working temp.of bearing shourld not be over 95?(thermometer method). cooling method: ic411 ex certification applies to a fix speed motor without frequency convertor. *direct starting under range -40?~15? is prohibited, appropriate meaures should be taken to preheat motors to keep the temperature on the motor enclosure above -15?by space heaters and heating stator windings with low voltage supply for a certain time.this direst current generating in the windings shall not exceed the rated current on the n

?????????????????

?????ic411 ????????1000m ???-15?-40? ????????? ?????220-240v 380-420v 660-690v ?????50hz/60hz ???????s1? ?????nsk??

????abb?? m2gp???????????

??????? 15052229077

相关产品:abb电机、西门子电机、abb变频电机、西门子贝得电机、西门子伺服电机、abb普通电机

(责任编辑:无锡鸿良自动化设备有限公司)