

SKF紧凑型电动插筒泵柱塞ECP1 – 1WAA22 – 000000电动泵

产品名称	SKF紧凑型电动插筒泵柱塞ECP1 – 1WAA22 – 000000电动泵
公司名称	合肥双合智能科技有限公司
价格	.00/件
规格参数	
公司地址	合肥市包河区锦绣大道3665号
联系电话	0551-65319662 15375267440

产品详情

exchange standard cartridges with 120 or 380 ml. It is compatible with oil viscosities from 20 to 1 500 mm²/ s and fluid grease grades of NLGI 00 and 000. ECP is a adaptable pump because it has 2 outlets, that can serve two lubrication lines simultaneously.

features and benefits

Reduces unplanned downtime and extends maintenance intervals

Suitable for use with SKF oil and fluid grease metering devices

Minimizes environmental impact via efficient use of lubricants

Minimizes risk of using wrong or contaminated lubricant

Fill-level monitoring with pre-warning functionality

Energy efficient 24 V DC operating voltage

Optional reservoir or cartridge design

Easy to install and operate

applications

Injection molding machines

Automotive (E-Mobility)

Lifts and lifting systems

Material handling

Industrial robots

Machine tools

Linear guides

PREFILLED CARTRIDGES To eliminate the risk of lubricant contamination, SKF recommends the ECP version that utilizes an integrated level switch to monitor fill level. The cartridges are pre-filled with fluid grease type 000

PLASTIC RESERVOIRS FOR EASY REFILLING Users preferring flexible reservoir sizes and easy refilling processes should select capacities of 0,5; 1,0 or 1,7 litres. Oil reservoirs include standard filling filter

TECHNICAL DATA

Function principle

Lubricant Oil Fluid grease

Number of lubricant outlets

Outlet pressure

Delivery volume Oil Fluid grease

Operating temperature

Motor voltage

Protection class

Capacity of the cartridge

Capacity of plastic reservoirs

Outlet connection

Dimensions without cartridge with cartridge with fixed

Mounting position

ORDER EXAMPLE The product can be configured

ECP1-1WAA22-1F1000