

# 西门子KTP400 舒适型

产品名称	西门子KTP400 舒适型
公司名称	浔之漫智控技术（上海）有限公司西门子一级代理商
价格	86.00/台
规格参数	西门子模块:西门子plc模块 西门子变频器:西门子一级代理商 西门子触摸屏:西门子触摸屏
公司地址	上海市松江区石湖荡镇塔汇路755弄29号1幢一层A区213室
联系电话	15618722057 15618722057

## 产品详情

公司在经营活动中精益求精，具备如下业务优势：

### SIEMENS 可编程控制器

- 1、 SIMATIC S7 系列PLC：S7-200、S7-1200、S7-300、S7-400、ET-200
- 2、 逻辑控制模块 LOGO！230RC、230RCO、230RCL、24RC、24RCL等
- 3、 SITOP直流电源 24V DC 1.3A、2.5A、3A、5A、10A、20A、40A可并联。
- 4、 HMI，屏TD200 TD400C K-TP OP177 TP177,MP277 MP377,

### SIEMENS 交、直流传动装置

- 1、 交流变频器 MICROMASTER系列：MM420、MM430、MM440、G110、G120.
- 2、 全数字直流调速装置 6RA23、6RA24、6RA28、6RA70、6SE70系列

### SIEMENS 数控 伺服

SINUMERIK:801、802S、802D、802D SL、810D、840D、611U、S120

及伺服电机，力矩电机，直线电机，伺服驱动等备件销售。

信誉\*，客户是公司成立之初所确立的宗旨，在公司的严格要求和员工们不折不扣地贯彻执行下发展延续至今。“假一罚十”一直是我公司的承诺。 承诺一：1、保证全新\*

承诺二：2、保证安全准时发货

承诺三：3、保证售后服务

流程一：1、客户确认所需采购产品型号

流程二：2、我方会根据询价单型号查询价格以及交货期，拟一份详细正规报价单

流程三：3、客户收到报价单并确认型号无误后订购产品

流程四：4、报价单负责人根据客户提供型号以及数量拟份销售合同

流程五：5、客户收到合同查阅同意后盖章回传并按照合同销售额到公司行

流程六：6、我公司财务查到款后，业务员安排发货并通知客户跟踪运单

您随口的一问多少钱，我就立马放下筷子赶紧回话。

您随口的一句有没有现货，我就立马进去拼命地找。

您随口问了问能优惠不？我就到处想办法。

您很随便，我却很当真；您不知道我的回答，只为您的满意.....

只因为我和您不止是客户的关系，而是把您当我的朋友，在全力以赴做到我能做到的

您的选择您的支持是我zui大的动力！————致我亲爱的客户（好朋友）

产品简述：质保一年，一年内因产品问题免费更新产品不收取任何费用

前瞻聚力，同心致远

西门子正是前行路上能共担风雨的伙伴。从一颗葡萄到一滴美酒的美妙变迁能在西门子数字化平台上全程追溯。而在2016年汉诺威博览会上，也源自西门子的前沿数字技术。

凭借\*技术、产品线、覆盖200多个的网络、金融解决方案及灵活服务，西门子在电力、油气与化工、矿山与工业等领域与EPC企业携手前行。

截至2015年底，西门子已与能建、电建、中石油、中石化、中材集团、中集来福士等上百家EPC企业在近60个合作项目，足迹遍及六大洲。

电源谐波滤波器以带有坚固外壳的部件形式提供。它们安装在客户提供的低压配电设备与变频器之间。电压在客户低压开关柜中进行分断并用熔断器进行保护。

电源谐波滤波器不使用风扇进行冷却（自然对流）。这意味着无需使用外部电源。

电源谐波滤波器配有一个可从外部的浮置恒温开关，用于热过载状况（例如，因送入的冷却空气不足而引起）。

注：要使用电源谐波滤波器，变频器必须具有一个电源电抗器。

Example: SINAMICS G120, frame sizes FSA, F and FSC; each with Power Module, CU240E2 F Control Unit and

Basic Operator Panel BOP-2 Example: SINAMICS G120, frame sizes FSD, FSE and FSF; each with Power Module, CU240E2 F Control Unit and

6SE0100-1AC15-5AA7 SINAMICS G180 2T2A-07400-002 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 2,2KW (400V) HWD W/O OPT. 410\*165\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC17-0AA7 SINAMICS G180 2T2A-07400-003 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 3KW (400V) HWD W/O OPT. 410\*165\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC21-0AA7 SINAMICS G180 2T2A-07400-004 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 4KW (400V) HWD W/O OPT. 410\*165\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC21-3AA7 SINAMICS G180 2T2A-07400-005 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 5,5KW (400V) HWD W/O OPT. 410\*165\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态

6SE0100-1AC21-8AA7 SINAMICS G180 2T2A-07400-007 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 7,5KW (400V) HWD W/O OPT. 510\*165\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC22-5AA7 SINAMICS G180 2T2A-07400-011 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 11KW (400V) HWD W/O OPT. 510\*165\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC23-7AA7 SINAMICS G180 2T2A-07400-015 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 15KW (400V) HWD W/O OPT. 610\*225\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC24-8AA7 SINAMICS G180 2T2A-07400-022 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 22KW (400V) HWD W/O OPT. 610\*225\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC25-8AA7 SINAMICS G180 2T2A-07400-030 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 30KW (400V) HWD W/O OPT. 610\*225\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2 组态 6SE0100-1AC27-8AA7 SINAMICS G180 2T2A-07400-037 230-500V, TN/TT 50/60 HZ TYP.MOTORPOWER 37KW (400V) HWD W/O OPT. 710\*350\*320MM IP20 AIRCOOLED, 6 PULSE MAINS LINE CHOKE, DV/DT FILTER EMC EN61800-3 FILTEREN55011 CL A, FIRST ENVIRONMENT C2

## 西门子变频器V20系列订货号

名称 订货号 货期 380V带内置进线滤波器 0.37KW/FSA 6SL3210-5BE13-7CV0 现货 0.55KW/FSA 6SL3210-5BE15-5CV0 现货 0.75KW/FSA 6SL3210-5BE17-5CV0 现货 1.1KW/FSA 6SL3210-5BE21-1CV0 现货 1.5KW/FSA 6SL3210-5BE21-5CV0 现货 2.2KW/FSA 6SL3210-5BE22-2CV0 现货 3KW/F 6SL3210-5BE23-0CV0 现货 4KW/F 6SL3210-5BE24-0CV0 现货 5.5KW/FSC 6SL3210-5BE25-5CV0 现货 7.5KW/FSD 6SL3210-5BE27-5CV0 现货 11KW/FSD 6SL3210-5BE31-1CV0 现货 15KW/FSD 6SL3210-5BE31-5CV0 现货 380V不带内置滤波器 0.37KW/FSA 6SL3210-5BE13-7UV0 现货 0.55KW/FSA 6SL3210-5BE15-5UV0 现货 0.75KW/FSA 6SL3210-5BE17-5UV0 现货 1.1KW/FSA 6SL3210-5BE21-1UV0 现货 1.5KW/FSA 6SL3210-5BE21-5UV0 现货 2.2KW/FSA 6SL3210-5BE22-2UV0 现货 3KW/F 6SL3210-5BE23-0UV0 现货 4KW/F 6SL3210-5BE24-0UV0 现货 5.5KW/FSC 6SL3210-5BE25-5UV0 现货 7.5KW/FSD 6SL3210-5BE27-5UV0 现货 11KW/FSD 6SL3210-5BE31-1UV0 现货 15KW/FSD 6SL3210-5BE31-5UV0 现货 220V带内置进线滤波器 0.12KW/FSA 6SL3210-5BB11-20 8周 0.25KW/FSA 6SL3210-5BB12-50 8周 0.37KW/FSA 6SL3210-5BB13-70 8周

0.55KW/FSA 6SL3210-5BB15-50 8周 0.75KW/FSA 6SL3210-5BB17-50 8周 1.1KW/F 6SL3210-5BB21-10 8周  
1.5KW/F 6SL3210-5BB21-50 8周 2.2KW/FSC 6SL3210-5BB22-20 8周 3.0KW/FSC 6SL3210-5BB23-00 8周  
220V不带内置进线滤波器 0.12KW/FSA 6SL3210-5BB11-2UV0 8周 0.25KW/FSA 6SL3210-5BB12-5UV0 8周  
0.37KW/FSA 6SL3210-5BB13-7UV0 8周 0.55KW/FSA 6SL3210-5BB15-5UV0 8周 0.75KW/FSA  
6SL3210-5BB17-5UV0 8周 1.1KW/F 6SL3210-5BB21-1UV0 8周 1.5KW/F 6SL3210-5BB21-5UV0 8周 2.2KW/FSC  
6SL3210-5BB22-2UV0 8周 3.0KW/FSC 6SL3210-5BB23-0UV0 8周 附件 参数下载器 6SL3255-0VE00-0UA0 8周  
BOP (基本操作面板) 接口模块 6SL3255-0VA00-2AA0 现货 制动模块230V 8A, 400V 7A  
6SL3201-2AD20-8VA0 8周 V20 BOP (基本操作面板) 6SL3255-0VA00-4BA0 现货  
BOP (基本操作板) 3米电缆 6SL3256-0VP00-0VA0 现货 SIMATIC内存卡 (SD内存卡)  
6ES7954-8LB01-0AA0 现货 RS-485终端电阻 (数量: 50个) 6SL3255-0VC00-0HA0 8周

### SINAMICS 驱动控制图 (SINAMICS DCC)

通过可配备的闭环控制、算术和逻辑块来扩展设备的功能范围, 并提供可以在 SINAMICS 驱动中以图形组态工艺功能的。SINAMICS DCC 是实现工艺功能的\*阶段, 作为 STARTER 调试工具的附加组件进行安装。

SINAMICS DCC 可让用户根据机器设备的具体功能, 在更大功能范围内对进行。SINAMICS DCC 对可用的功能数量没有。功能的数量仅受控制单元的能力。

SINAMICS DCC 适用于以下 SINAMICS 驱动:

SINAMICS G130 SINAMICS G150 SINAMICS S120 SINAMICS S150 SINAMICS DCM SINAMICS DCP  
SINAMICS GM150 SINAMICS 150 SINAMICS GL150 SINAMICS SL150

通过用户友好的 DCC 编辑器, 可基于图形进行组态, 能够清晰表示控制回路结构, 并且已创建的图表具有较高的可再用性。

开环和闭环控制功能通过库 (DCB 库) 中的多背景块 (驱动控制块 (DCB)) 来定义; 通过拖放, 可以选择驱动控制块并以图形进行链接。通过和诊断功能, 可以验证程序性能, 并在发生故障时确定其原因。

提供了两种类型的 DCB 库, 即: DCB Standard 和 DCB Extension。随 SINAMICS DCC 提供的 DCB Standard 库包含大量闭环、算术和逻辑块以及的开环和闭环控制函数。

为了逻辑组合、分析和获取数字量, 所有常用逻辑功能均可供选择 (AND、XOR、开/关、RS 触发器、计数器等)。各种算术功能 (如值生成、除法器 and 最小值/最大值评估) 可用来监控和分析数值量。除闭环驱动控制外, 还可方便地组态轴向卷绕机功能、PI 控制器、斜坡函数发生器或发生器。

除库外, 随 SINAMICS DCC 还提供了 DCB Extension 库 (V4.6 及更高固件版本)。其中包含更广泛的块, 可在 DCC Editor 中用作附加的库。

DCB Extension 以 GMC

库的形式提供了新的运动控制块, 以算术扩展库的形式提供了算术和逻辑功能。

使用这些块, 可以通过 SINAMICS DCC 实现以下应用: