

VF-3/7 型空气压缩机

| | |
|------|---------------------------------------|
| 产品名称 | VF-3/7 型空气压缩机 |
| 公司名称 | 自贡山川气体压缩机有限公司 |
| 价格 | .00/个 |
| 规格参数 | 压缩介质:空气 工作原理:活塞式压缩机 润滑方式:少油注油润滑 |
| 公司地址 | 自贡市贡井区贡雷路79号 |
| 联系电话 | 0813-3305696 18708315256 |

产品详情

| | | | |
|--|---------------|----------------|---------------------------|
| 压缩介质 | 空气 | 工作原理 | 活塞式压缩机 |
| 润滑方式 | 少油注油润滑 | 品牌 | 山川牌 |
| 用途 | 风动工具、矿用压缩机、其他 | 型号 | VF-3/7 |
| 功率 | 18 (Kw) | 冷却方式 | 风冷式 |
| 传动方式 | 联轴器传动 | 产品类型 | 全新 |
| 型式 | 固定式压缩机 | 排气量大小 | 小型 |
| 排气压力 | 0.7 (MPa) | 外形尺寸 (长*宽*高) | 2170 × 1330 × 1230 (mm) |
| 性能 | 低噪音 | | |
| vf-3/7型空气压缩机vf-3/7 type air compressor | | | |

用途及适用范围 application and usage

该压缩机主要为风动机械、风动工具提供稳定气源，广泛用于矿山开采、建筑施工、轻工建材、机械制造等行业，以及为工矿企业内使用压缩空气和带动风动工具、风动机械使用，具有高效、节能、安全、可靠的特点。

the air compressor mainly provide the stable gas source for the pneumatic machine and tool, and applicable for mineral exploitation, building construction, lighting material, mechanical manufacturing, traffic transportation, also it is used to serve for air compression, pneumatic tool and machine in mineral industrial factories. merits: high efficiency, energy saving, safety, and security.

主要技术参数main technical parameter

压缩机 compressor

容积流量(cubage flow) : 3 m³ /min

额定排气压力(rated exhausting gas pressure) : 0.7 mpa

转速(rotational speed) : 970 r/min

轴功率(power from the shaft) : 18 kw

气缸数×气缸直径(no. of cylinder × diameter of cylinder) : 1 × 210/1 × 125mm

重量(weight) : 1100kg

外形尺寸(长×宽×高)(overall dimensions) (l × w × h) : 2170 × 1330 × 1230 mm

电动机 motor

型号(type) : y200l1-6

转速(rotational speed) : 970 r/min

功率(power) : 18.5 kw

额定电压(rated voltage) : 380v

储气罐 gas tank

v-3/7-85-0 , 筒体直径(diameter of main body) 400mm

启动器 starter

qxj-25

型式及特点pattern and character

本机型为v型、两列、两级、风冷的固定式往复活塞空气压缩机。空压机与储气罐一体化。安装、使用、方便、省时。

this machine vf-3/7 is of v model, double-row, double-step, fan-cooling, fixed reciprocating piston type air compressor. air compressor is integrated with gas tank, easy, convenient to mount and operate.