

北京布莱迪精密压力表

产品名称	北京布莱迪精密压力表
公司名称	北京布莱迪仪器仪表有限公司西安办事处
价格	面议
规格参数	品牌:北京布莱迪 型号:YB-150/120/80
公司地址	中国 陕西 西安市莲湖区西大街桥梓口唐人街小区1504室
联系电话	086-029-87364011 18729506066

产品详情

产品简介:

精密压力表可用来检验工业用普通压力表，亦可直接用于对介质压力的高精度测量。

yb 型系列精密压力表可在对铜合金无腐蚀性的场所中使用。

ybh型系列则适用于多种腐蚀性的环境场所，可对具有腐蚀性的介质中进行高精度的测量。

150系列精密压力表采用mpa刻度值直接读取盘面。包括有径向、轴向及径向带边、轴向带边多种安装形式。

yb技术参数 yb
technical specifications

精度等级：0.25%；0.4%
accuracy: 0.25%；0.4%

测量范围：0.1 至 100mpa
range: 0.1 to 100mpa

波登管/ 接头 : 0-10mpa为磷青铜 c 型波登管与
10mpa-to- tin welding between phosphor bronze

burdon tube:

黄铜接头锡焊接。

c-type burdon tube and brass.

仪表机芯 : 铜合金带宝石轴承

movement: copper alloy

仪表连接 : m20 × 1.5 外螺纹

connection: m20 × 1.5 out thread(other standard

(可选其他标准连接)

connections available)

仪表外壳 : 铁喷黑塑

case: steel with black ptfе

防爆片材质 : 橡胶

blast-proof flake: rubber

仪表度盘 : 不锈钢双层镜面 , 带有调零装置。

stainless steel double glasses, with zero adjustable set.

dial:

表针 : 65mo锰 , 黑色刀锋式

pointer: 65mo, steel, knife end

ybh技术参数 ybh

technical specifications

测量范围 : 0~160mpa

range: 0~160mpa

波登管/ 接头 : 0- 至 -10mpa不锈钢c 型波登管

tube/socket: 0-to- 10mpa argonarc welding between stainless

burdon

与不锈钢接头氩弧焊接 ;

steel c-type burdon tube and stainless steel socket.

16-至 -160mpa不锈钢螺旋波登管 1

6-to-160mpa argonarc welding between stainless steel helical

与不锈钢接头氩弧焊接。

tube and stainless steel socket.

仪表外壳 : 不锈钢 本色

case: stainless steel, original colour

其他 同 yb

other features as yb