

公称压力Nominal pressure

PN

壳体试验Casing test

1.5XPN

密封试验Leak test

1.1XPN

工作温度Operating temperature

橡胶 80 四氟密封 180 硬密封 425 Rubber
80 , PTFE 180 , hard sealing 425

适用介质Working medium

糖浆、纸浆、污水、煤浆、灰、渣水混合物Syrup, p
sewage, coal slurry, dust, slag-water mix

手动无隙刀型闸阀、耐磨浆液阀、无间隙刀闸阀主要外形及连接尺寸 Profile and connection
dimension 单位 Unit:mm

公称压力Nominal pressure(MPa)	公称通径Nominal through diameter (mm)	L	D	D1	D2	H	N-M	
1.0	50	48	160	125	100	285	4-M16	1
	65	48	180	145	120	298	4-M16	1
	80	50	195	160	135	315	4-M16	2
	100	50	215	180	155	365	8-M16	2
	125	57	245	210	185	400	8-M16	2
	150	57	280	240	210	475	8-M20	2
	200	70	335	295	265	540	8-M20	3
	250	70	390	350	320	630	12-M20	3
	300	76	440	400	368	780	12-M20	4
	350	76	500	460	429	885	16-M20	4
	400	89	565	515	482	990	16-M22	4
	450	89	615	565	532	1100	20-M22	5
	500	114	670	620	585	1200	20-M22	5
	600	114	780	725	685	1450	20-M27	6
700	130	895	940	800	1700	24-M27	6	