

# 四川 四脚防浪块模具 四角空心块模具

产品名称	四川 四脚防浪块模具 四角空心块模具
公司名称	河北宏旭模具制造有限公司
价格	400.00/套
规格参数	品牌:宏旭模具 加工能力:每天 物流周期:3天
公司地址	河北省保定市莲池区东金庄乡后辛庄村
联系电话	15720001423 15720001423

## 产品详情

四脚防浪块模具通常由四个角部组件、底部组件和顶盖组件组成。每个角部组件都包括一个直角三角形的前板和一个斜边形的后板，前板上设置有通孔，后板上设置有与通孔相对应的凸起。底部组件由一个底板和四个立柱组成，底板上设置有与四个通孔相对应的四个凹槽，立柱上设置有与四个凸起相对应的四个螺纹孔。顶盖组件则包括一个顶板和四个斜支撑杆，顶板上设置有中心孔，斜支撑杆上设置有与四个凹槽相对应的四个螺纹孔。通过预制的方式进行预制件的加工制作，每个钢模具的长度大概在一米左右，在钢模具拼接完成后进行相关检查，需要在钢模具内外壁上涂油，并且通过现场浇筑灌浆进行脱模操作。成型的防浪块预制件则可以根据施工现场要求进行排列摆放，并且可以借助分割、焊接、拼接和打磨等生产工艺来组成不同的形状，这些防浪块或者是其他形式的防浪块在施工现场只需要简单的吊装即可，不需要多余的施工工序。在施工现场，防浪块模具摆放整齐后进行位置的调节，然后保持内外壁的美观度后即可正常施工使用了。需要注意的是要防止发生模具变形的现象出现，以免模具的使用次数受到一定的影响，模具的表面也会焊接上一层筋板来作为对模具的一层加固，让模具更加的坚硬，耐用，使用的时间长久，模具的清洁，所使用的是清洁剂来进行的，只要是把模具的表面清理干净就能方便下次对模具的使用。The four-legged wave block mold usually consists of four corner components, a bottom assembly, and a top cover assembly. Each corner assembly comprises a right-angled triangle front plate and a beveled rear plate with a through hole on the front plate and a protrusion corresponding to the through hole on the rear plate. The bottom assembly is made up of a base plate and four columns, the bottom plate is provided with four grooves corresponding to the four through holes, and the column is provided with four threaded holes corresponding to the four protrusions.