

美国派克PARKER DA400S磁粉探伤仪

产品名称	美国派克PARKER DA400S磁粉探伤仪
公司名称	上海耀壮检测仪器设备有限公司
价格	面议
规格参数	类型:磁粉探伤仪 品牌:美国Parker/派克
公司地址	中国 上海市徐汇区 漕东支路111弄4号楼1401室
联系电话	86 021 51086370 13818810982

产品详情

美国派克便携式da400s磁粉探伤仪：美国parker公司磁粉探伤仪da-400采用了许多先进技术来形成感应磁场，具有极高通用性，固定的ac或dc磁场，用于表面和近表面缺陷的检测，是控制器与固态电子器件为一体的高性能的轻便仪。可疴高能磁场集中施加到检测区，快速准确发现材料缺陷。磁极可将a c或dc磁场施加到各种形状工件的检测区域，没有电弧烧伤。

da400s磁粉探伤仪的技术参数：

型号	da400	da400s
电源	110vac 50-60hz	230vac 50-60hz
电流	4a	3a
磁场	交流	交直流
工作周期	2分钟开/关	2分钟开/关
重量	3.68kg	3.68kg
尺寸	188*235*54mm	188*235*54mm
磁极间距	0-305mm	0-305mm
电缆	3芯2m长电缆	3芯2m长电缆

da-400 series contour probes®

the da-400 contour probe is a portable, self-contained instrument designed to produce a magnetic field on or within ferro-magnetic materials.

the selective ac and pulsed dc functions are built into a single reliable instrument. the ac mode produces an intense ac field for detection of surface defects and demagnetizing after inspection. the dc mode produces an intense pulsed dc field for detection of some subsurface defects.

controls and solid-state electronics are contained within the high impact molded housing. articulating legs allow the ac

or dc field to be applied to the precise area of inspection on nearly any part of the surface shape... in the lab, factory or field site.

all parker contour probes comply with the requirements of applicable specifications. certified for european ce requirements.

versatility and powerful performance in a lightweight (8 lbs.) instrument constant ac or pulsed dc fields with the flip of a switch for the location of surface and some sub-surface defects apply continuous or residual magnetic fields and demagnetize to use with dry powder, wet fluorescent or visible high impact molded housing one year repair/replacement guarantee

da-400s series contour probes® specifications

electronics	reliable solid state circuitry contained within molded housing
mechanical capacity	minimum-maximum distance across poles: 0 to 12" (0-305mm)
fields – selective	ac: constant level dc: pulsed dc flux density approximately 68,000 lines per square inch at 4" pole spacing. (50 pound pull.)
power source	105-230 vac, 50-60 hz, 4 amps 3-connector power cord and plug. (available in export voltages.)
controls	1 momentary, push to test 2 ac/dc selector switch
weight	3.4kg
finish	injection molded housing glass filled nylon®

本产品的加工定制是否，类型是磁粉探伤仪，品牌是美国Parker/派克，型号是DA400S，测量范围是0 ~ 305mm，分辨率是0，尺寸是188 × 235 × 54 (mm)，重量是3.68 (kg)