

久巨MAG-1520麻将充磁机

产品名称	久巨MAG-1520麻将充磁机
公司名称	深圳市久巨电子技术有限公司
价格	面议
规格参数	品牌:久巨 型号:MAG-1520
公司地址	中国 广东 深圳市 深圳市宝安区沙井街道新和大道西二号5楼
联系电话	86 0755 29351099 13428976919

产品详情

“ mag系列 ” 充/退电源 mag" series charge / demagnetization power

磁性材料被广泛应用于家电、汽车、铁路、航空航天、电力、钢铁等领域。mag电容型脉冲式充磁机有着快速高效的优点，对磁性材料的着磁基本采用此类设备。公司产品以稳定的性能，优良的安全保障，在业内树立起品牌的标杆，深受国内外广大客户信赖。

本产品采用电容作为能量集结源,脉冲式放电输出，用这种方式得到小电流输入，大电流输出，通过充磁线圈，对磁性材料进行充磁，以plc可编程控制器为核心的测量-控制装置对电容充电、储能和输出等执行控制，放电周期和输出电压均可设定、调节。

(magnetic materials are widely used in the appliance, automotive, rail, aerospace, electric power, iron and steel and other fields.mag capacitive pulse magnetizing machine has the advantages of fast and efficient, and magnetic materials with magnetic basic use of such equipment. the company's products with stable performance, excellent security in the industry to establish the benchmark of the brand by the trust of our customers at home and abroad.this product uses capacitors as energy build-source, pulse discharge output, input this way, a small current, high current output, through the magnetizing coils, the magnetization of magnetic materials, plc programmable controller as the core measurement - control means charging the capacitor, the energy storage and output execution control discharge cycle, and the output voltage can be set and adjusted.)

mag系列，高压电容式充/退磁机 mag series, high-voltage capacitor charge/ demagnetization

特点：features:

采用光钎隔离脉冲控制技术，精确的电压集成控制芯片，并将充磁机内部的阻抗减低至极限状态，输出高效率的充磁电流，并将电流衰减时间缩至到最短的回路，使用一般的充磁机进行连续充磁的时候，因为充磁线圈温度的上升导致充磁线圈的损坏，或因温度的上升导致阻抗的上升，或因充磁电流的降低导致充磁的不充分等等，I型（低阻抗型）的产品可以将充磁线圈的热发生量抑制到原来的1/5左右，而且，对应于负荷动作的专门设定，也可以制作超低阻抗型。

lightthebrazingisolatedpulsecontrol technology,precisionvoltageintegratedcontrolchipandthemagnetizerinternalimpedanceto reduceto the limits ofstateoutputhigh efficiencyofthemagnetizingcurrent,andcurrent decaytimeisreduced tothe shortestloop,using thegeneralmagnetizerscontinuousmagnetizingwhenthe temperature rises, becausethemagnetizingcoilto causedamagetothemagnetizingcoils, orlead toariseinimpedanceduetothetemperature rise, ordueto the decreaseofthemagnetizingcurrentis not sufficienttocausemagnetizing,I-type (low impedance)of theproduct can beheatgeneration amountofthemagnetizingcoilis suppressed toabout1/5oftheoriginal,and,specifically setcorresponding to the loadoperation,alsocan produceultra-lowimpedance type.

我司可根据客户不同的要求，设计制作200-4000v,500uf—100,000uf的各种不同功率的充退磁设备。

division i according to the different requirements of our customers, designed 200-4000v, demagnetization 500uf-100000uf of, various power equipment.

代表性的充磁设备型号及参数表

representative of the magnetized device model and parameter table

充退磁机demagnetizationmachine	1000v-3500v系列 1000v-3500v series			
型号model	mag-1520	mag-2020	mag-2520	mag-3550
电源power supply	220v	220v	380v	380v
充电时间charging time	1-1.5s	1-2.0s	1-3.0s	1-6.0s
输出电压output voltage	dc50-1500v	dc50-2000v	dc50-2500v	dc50-3500v
电容容量capacitance	2000uf	2000uf	2000uf	5000uf
输出能量 output energy	2250j	4000j	6250j	30625j
最大电流maximum current	10.000a	20.000a	30.000a	40.000a
外形尺寸maximum current	120*55*80	120*70*80	120*80*80	110*80*150
重量weight	180kg	200kg	260kg	600kg

基本性能basic performance

可控电压直流脉冲输出 • the controllable voltage dc pulse output

电源指示、电容容量指示、输入电压指示、充电结束指示、输出电压指示、放电电流指示the power indicator, capacitance indicates input voltage indication, the end of charge indication, indication of the output voltage, the discharge current indication

放电周次计数discharge cycles count

外部信号控制external signal control

紧急停止，内部放电保护（设备被打开、充电超时、待机超时）emergency stop the internal discharge protection (the device is opened, charging timeout, standby timeout)

• 选用功能：optional features:

选用三相与两相供电（大能量设备要求提高充电速度）充退磁一体机 • selection of the three-phase and two-phase power supply (large energy equipment requirements to improve the charging speed) demagnetization one

多路输出，手动充电，输出极性切换 • multiple output manually charging output polarity switch

电容器分级组合，容量采取闸刀切换capacitor classification combination, the capacity to take the knife switch

分步放电功能（适用对材料进行定位的充磁，一般为分低、高二次充电） • step-by-step discharge function to locate the material (for magnetizing, generally divided into low-, high-rechargeable)

反峰切除功能（推荐配合多级线圈使用）anti-function peak resection (recommended with multiple coil use)

触摸屏（去除面板的指令键和表头等显示，集合在液晶屏上显示和作用）touch screen (remove panel instruction key and meter etc show that set displayed on the lcd panel and role)

本产品的加工定制是是，品牌是久巨，型号是MAG-1520，电源电压是220（V），消耗功率是10K（W），充磁电压是2000（V），磁极组尺寸是60（mm），磁极尺寸是10（mm），磁钢尺寸是40（mm）