

精密露点仪 上海贸创

产品名称	精密露点仪 上海贸创
公司名称	上海贸创电气有限公司
价格	面议
规格参数	品牌:上海贸创 型号:MC-LD
公司地址	中国 上海市宝山区 上海市宝山区水产路2600弄67号101
联系电话	86 021 60510607/65893883 15800561319

产品详情

mc-ld型精密露点仪

一、主要特点
零点自动校准独有的超大储存功能
首创的电量显示操作简单、携带方便
重复性好、响应速度快
全量程单点法露点校准斜率自动校准独特的大屏显示
先进的探头保护功能抗污染、抗干扰
灵敏度高、稳定性好
二、技术指标
测量范围：露点-80 ~ +20 ，（支持ppmv等）
露点精度：±0.2 （当露点温度低于0 ，传感器输出为霜点）

响应时间63% [90%] +60 -20 5s [45s] -20 -60 10s [240s] 分辨率：

露点0.1 或0.1ppm 重复性：±0.2

气体流量：sf6调节在0.5 ~ 0.9l/min，h2调节在0.1 ~ 0.4l/min 压力测量：0 ~ 1.0mpa

探头保护：不锈钢烧结过滤网 工作电压：

110 ~ 220vac，交直流两用 储存温度等级：-40 ~ +70 输出接口：usb1.1 规范操作环境：温度：

-35 ~ +60 压力：0 ~ 20bar 样气流速：无影响

其它配置：标准版管理软件，含报表打印，湿度常用转换工具包 电子质量流量计

锂电池，交直流电两用，自动切换，过充过放保护功能

mc-ld precision dewpoint meter first, the main features of automatic zero calibration the unique oversized storage function first power display easy to operate, easy to carry repeatability, fast response full-scale single-point method dew point calibrations slope automatic calibration unique large-screen display advanced probe protection anti-pollution, anti-jamming high sensitivity, good stability second, technical indicators measuring range: dew point of -80 ~ +20 , (support ppmv) dew point accuracy: ± 0.2 (when the dew point temperature is below 0 ° c, the sensor output frost point) response time 63% [90%] +60 -20 5s [45s] -20 -60 10s [240s] resolution: 0.1 dew point or 0.1ppm repeatability: ± 0.2 gas flow rate: sf6 adjusted within 0.5 ~ 0.9l/min, h2 adjusted within 0.1 ~ 0.4l/min pressure measurement: 0 ~ 1.0mpa probe protection: stainless steel sintered filter operating voltage: 110 ~ 220vac, ac and dc storage temperature rating: -40 ~ +70 output interface: usb1.1 specification operating environment: temperature: -35 ~ +60 pressure: 0 ~ 20bar sample gas flow rate: no effect on other configurations: the

standard version of the management software, with report printing, humidity commonly used conversion kit
electronic mass flowmeter lithium battery, ac and dc dual-use, automatic switching, overcharge and over discharge
protection function

本产品的加工定制是是，品牌是上海贸创，型号是MC-LD，类型是在线露点变送器，测量范围是露点-80
~ +20 ，测量精度是0.2，测量对象是精密露点仪，温度范围是-35 ~ +60 ()，分辨率是露点0.1 或0.
1ppm重复性：±0.2 ，尺寸是300X200X180 (mm)，电压是110 ~ 220 (v)，电源是交直流两用