

# 导热油加热的2.1MPa6m<sup>3</sup>;再生胶动态脱硫罐

产品名称	导热油加热的2.1MPa6m <sup>3</sup> ;再生胶动态脱硫罐
公司名称	河北金梆子锅炉有限公司
价格	面议
规格参数	品牌:金梆子 型号:ZT 6.0R
公司地址	中国 河北 石家庄市 河北省石家庄市石清公路66号
联系电话	86 311 82296564 13931885746

## 产品详情

### 再生胶动态脱硫罐

一，用途（use） 该产品用于将粉末状硫化胶与软化剂、活化剂及水等置于罐内，在连续搅拌下密闭加热，以使胶粉达到均匀有效胶硫目地，是采用高温动态脱硫新工艺的关键设备。 this product is used for that in order to reach even and effective desulfidation for rubber powder, put pulverous crosslinked rubber,

softener, activator and water into the pot ,heat hermetically and mix continuously, adopted key equipment for the technology of high

temperature dynamic desulfidation.

二，特点(characteristics): 该产品为卧式ii类压力容器，用导热油加热。罐口开关门有全自动和手动二种形式供用户选择。罐体上部为加料口、下部为出料口。全自动动态罐开关门由液压控制。手动动态罐开关门采用人工机械错口手动开关门，以上两种动态罐均与零压开关连锁，确保安全。搅拌器由jqzq系列减速器通过双排链轮传动或直给式转动，正反转可自动控制。搅拌浆形式为带状与附壁组合式。压力容器部件按gb150-98《钢制压力容器》标准设计、制造。由河北省锅炉压力容器监督检测所监检验收。 this product is a horizontal pressure vessel type ii, heats up with the heat conduction oil. customers could select two ways-automatic and manual operation for pot gate opening and closing. upside of the pot is charge port, and downside is discharge port.

full autodynamic pot opening and closing gate is controlled by hydraulic pressure. adopt manual mechanical alternate out hand

opening and closing gate for the manual dynamic opening and closing gate. above two dynamic pots are linked to the zero pressures

with to ensure safety. adopt jzq series reducer through double row chain wheel rotating or direct driving for the blender, positive

and negative rotating could be controlled automatically. the shape of mixing propeller is assorted of ribbon and mural. the parts of

pressure vessel are designed and manufactured according to bg150-98 “ steel pressure vessel ” and have been inspected examination and approved by. hebei province technology inspection office

of boiler and pressure vessel.

动态脱硫罐性能参数（2.1mpa）：

参数 parameter内容content	型号 model			
	zt 3.3r	zt 4.5r	zt—6r	zt-
设计压力design pressure	2.1mpa	2.1mpa	2.1mpa	2.1
工作压力working pressure	1.8mpa	1.8mpa	1.8mpa	1.8
设计温度design temperature	2170c	2170c	2170c	21
工作温度working temperature	2120c	2120c	2120c	21
有效容积active volume	3.0m <sup>3</sup>	4.5m <sup>3</sup>	6m <sup>3</sup>	8m
搅拌器转速rotate speed of blender	16r/min	16r/min	15r/min	15r
夹套容积jacket volume	0.72m <sup>3</sup>	1.04m <sup>3</sup>	1.6m <sup>3</sup>	1.8
夹套设计压力design pressuer of jacket	0.1mpa	0.1mpa	0.1mpa	0.1
夹套工作压力working pressure of jacket	常压	常压	常压	常
加热方式heating method	导热油 heat conduction oil			
换热面积hear exchange area	8.18m <sup>2</sup>	12.55m <sup>2</sup>	15m <sup>2</sup>	17
电机功率motor power	15kw	18.5kw	18.5kw	30k

本产品的加工定制是是，品牌是金梆子，型号是ZT 6.0R，电动机功率是18.5（KW）