



no.	a no.	mm	mm	mm	mm	m m	mm	mm	kg/m	mm
*04c-1	*25	6.3 5	3.30	3.18	2.31	7.8 0	8.4 5	5.90	0.15	
*06c-1	*35	9.5 25	5.08	4.77	3.58	12. 15	13. 1	8.95	0.33	
085-1	41	12. 7	7.77	6.25	3.58	13. 75	15. 4	9.90	0.41	
08a-1	40	12. 7	7.95	7.85	3.96	16. 6	17. 75	11.90	0.62	
10a-1	50	15. 875	10.16	9.40	5.08	20. 90	22. 2	15.09	1.02	
12a-1	60	19. 05	11.91	12.57	5.94	25. 9	27. 5	18.0	1.50	
16a-1	80	25. 4	15.88	15.75	7.92	32. 80	34. 90	24.10	2.60	
20a-1	100	31. 75	19.05	18.90	9.53	40. 00	43. 20	30.10	3.91	
24a-1	120	38. 10	22.23	25.22	11.10	50. 45	53. 20	36.10	5.62	
28a-1	140	44. 45	25.40	25.22	12.70	54. 20	59. 00	42.10	7.50	
32a-1	160	50. 80	28.58	31.55	14.27	64. 30	69. 60	48.10	10.10	
36a-1	180	57. 15	35.71	35.48	17.46	72. 80	78. 60	53.60	13.45	
40a-1	200	63. 50	39.68	37.85	19.85	80. 30	87. 20	60.00	16.15	
48a-1	240	76. 20	47.63	47.35	23.81	95. 50	103 .00	72.39	23.20	
*04c-2	*25- 1	6.3 5	3.30	3.18	2.31	14. 50	15. 15	5.90	0.28	6.40
*06c-2	*35- 2	9.5 25	5.08	4.77	3.58	22. 5	23. 4	8.95	0.63	10.1 3
08a-2	40-2	12. 7	7.95	7.85	3.96	31. 1	32. 25	11.90	1.12	14.3 8
10a-2	50-2	15. 875	10.16	9.40	5.08	39. 00	40. 30	15.00	2.00	18.1 1
12a-2	60-2	19. 05	11.91	12.57	5.94	48. 80	50. 30	18.00	2.92	22.7 8
16a-2	80-2	25. 4	15.88	15.75	7.92	61. 90	64. 20	24.10	5.15	29.2 9
20a-2	100- 2	28. 58	19.05	18.90	9.53	76. 20	80. 50	30.10	7.80	35.7 6
24a-2	120- 2	35. 71	22.23	25.22	11.10	95. 40	99. 70	36.00	11.70	45.4 4
28a-2	140- 2	39. 68	25.40	31.55	12.70	13 0.1 0	107 .90	42.00	15.14	48.8 7

32a-2	160-47.	28.58	35.48	14.27	12	128	48.00	20.14	58.5	
	2	63			2.9	10			5	
					0					

本产品的是否进口是否，标准编号是420-1，类别是传动用短节距滚子链，材质是45#锰钢，适用范围是摩托车，品牌是东华自强，型号是420-1\*108L，链节距是12.7 (p)，链板厚度是1.5 (mm)，滚子直径是7.77 (mm)，销轴直径是3.96 (mm)，减速比是3，级数是多级，是否标准件是标准件，产品类型是传动链，样品或现货是现货，是否提供加工定制是是