

# Walnut shell filter 油田污水处理用核桃壳 污水过滤用核桃壳

产品名称	Walnut shell filter 油田污水处理用核桃壳 污水过滤用核桃壳
公司名称	温县宏发活性炭水处理有限公司
价格	面议
规格参数	滤料类型: 适用对象:水 用途:气液过滤
公司地址	温县北冷乡 工业政府工业区
联系电话	0086-037160268806 15938733855

## 产品详情

wenxian hongfa carbon co., ltd 温县宏发活性炭水处理有限公司 phone number 电话: 0086 0371 60268806

mobile phone 移动电话: 15938733855

fax 传真: 0086 0371 60268806

address 地址: 中国 河南 温县 温县北冷工业区

postcode 邮编: 454850

我厂生产的果壳滤料是采用山核桃壳为原料,经破碎、风旋、抛光、蒸洗、筛选加工而成,外观光泽,呈黄褐色。耐磨抗压,吸附能力强,抗油浸,不结块,不腐烂等特点,适用于油田、钢铁、冶炼、环保化工含油污水处理等行业的过滤装置。

常用规格: 0.5-0.8mm 0.8-1.2mm 1.2-1.6mm 1.6-2.0mm

the walnut shell filters material produced by our company with pecan shell as raw material, is processed and made by crushing, air rotary, polishing, steaming and washing, screening and other processes. it has a shiny brown appearance; also it has good compression strength, adsorption ability, anti-oil-immersed, non-caking, and non-rotting and other characteristics; it is used in oil, steel, metallurgy, environmental protection, chemical and other industry 's filter making. common specifications: 0.5-0.8 mm 0.8-1.2mm 1.2-1.6mm 1.6-2.0mm

核桃壳滤料采用优质山核桃壳为原料,经过破碎、抛光、蒸洗、药物防腐处理,两次筛选加工而成。此滤料坚韧、耐磨、抗压(抗压力为23.4kgf),化学性能稳定,吸附截污性强(吸附率为27-50%),抗油浸,易反洗再生,反冲洗强度低(6.7l/sm<sup>2</sup>),滤速快(24-26m/h),不板结,不腐烂,永不更换,每年只需补充5-10%即可。油去除率达95%,含油降至5mg/g以下。适用于油田、节油环保设备等方面。

检测项目	测试数据	检测项目	测试
油去除率	90-95%	反洗强度	25m3/m2.h
悬浮物去除率	95-98%	水冲洗压力	0.32mpa
滤速	20-25m/h	维护方式	每年补充5 - 10%
比重	1.5g/cm3	堆密度	0.8g/cm3

walnut shell material of high quality walnut shell as raw material, crushing, polishing, steam cleaning, drug preservative treatment, two filter processed.this filter tough, abrasion, pressure (anti-pressure 23.4kgf), chemical stability, absorption interception in strong (absorption rate of 27-50%), anti-immersion, easy backwashing and regeneration, backwashing low intensity(6.7l/sm<sup>2</sup>), the filtration rate fast (24-26m / h), does not harden, does not rot, will never change, just add 5-10% per year can be.oil removal rate of 95%, oil down to 5mg / g less.apply to oil, fuel-efficient environmental protection equipment and so on.

test item	test data	test item	test
oil removal efficiency	90-95%	backwashing strength	25m3/m2.h
suspended solids removal rate	95-98%	water flushing pressure	0.32mpa
filtration rate	20-25m/h	way of protecting	additional 5-10% per year
the proportion	1.5g/cm3	bulk density	0.8g/cm3

本产品的滤料类型是果壳，适用对象是水，用途是气液过滤，性能是耐酸,耐碱,耐高温,耐低温，类型是高效，品牌是HONGFA/宏发，吸附率是98.2（%），抗压力是10（kgf），密度是1.282（g/cm<sup>3</sup>），孔隙率是98.1（%），磨损率是0.37，硬度是3.5，化学成分是果壳，盐酸可溶率是97.0（%）