

月销3000滑动电位器SL10NV(3.3)直滑贴片电位器

产品名称	月销3000滑动电位器SL10NV(3.3)直滑贴片电位器
公司名称	世行有限公司
价格	面议
规格参数	品牌:WORLDWALK 型号:SL10NV(3.3)
公司地址	中国广东 佛山市顺德区 陳村鎮白陳路廣隆工業區37號三樓
联系电话	86-075723329891/23329892 13600320568

产品详情

適用於隨身帶的醫療儀器、汽車電子設備、報警系統等音量音質的調節

1.general

1.1application:this specification is applied to potentiometers used for electronic equipment.

1.2standard atmospheric conditions

unless otherwise specified,the standard range of atmospheric conditions for making

measurements and test is per the following limits:

ambient temperature : 15 to 35

relative humidity : 25% to 75%

air pressure : 86 kpa to 106 kpa

1.3operating temperature range : -10 to +50

1.4storage temperature range : -15 to +70

1.5suggested storage period : about 6 months

2 . electronic specification :

	item	conditions	specifi
2.1	total resistance	measurement shall be made by the resistance between terminal 1 and 3 with lever settled at terminal 1 or 3.	100K
2.2	total resistance tolerance		± 1
2.3	resistance taper	measurement shall be made by the resistance law method.measurement shall be made at the position of right diagram from the edge at the side of terminal 1.when based on terminal 3. from the edge at the side of terminal 3. out voltage between terminals1and2 ----- x 100% applied voltage between terminals 1and 3	
2.4	residual resistance		20 max.

2 . electronic specification :

	item	conditions	specifi
2.6	rated voltage	rated voltage $e = \sqrt{p \cdot r}$ (v) p: power rating r: nominal total resistance when the rated voltage exceeds the maximum operating voltage, the maximum operating voltage shall be the rated voltage	ac 1
2.7	rotational noise	dc 20v,when the rated voltage is 20v or less, its rated voltageshall be applied to the terminals between 1 and 3.and then the procedures, refer to iec 393-1-4.15 traveling speed:20=/sec	less than
2.8	insulation resistance	a voltage of 100vdc shall be applied for1min,after which measurement shall be made	50 m
2.9	withstand voltage	trip curr ant:2ma measuring frequency:50/60hz 250v ac for 1min.	without damage t arcing or br

3. mechanical specification :

	item	conditions	specifi
3.1	travel		10mm
3.2	sliding force		15 6
3.3	stopper strength		1kgf.c
3.4	sliding life		10,000 c

4. soldering conditions

4.1 manual soldering :

temperature of soldering iron : 300 or less.

application time of soldering iron :within 3s.

4.2 dip soldering

printed wiring board: single-sided copper clad laminate board with
thickness of 1.6mm .

flux:

specific gravity: 0.82 or more.

flux shall be applied to the board using a bubble foaming type fluxer

the board shall be soaked in the flux bubble only to the middle of its thickness.

flux shall not come into contact with the component side surface.

preheating:

surface temperature of board: 100 or less.

preheating time : within 2 min.

soldering:

solder temperature : 260 less.

immersion time: within 3 s.

dimensions尺寸图/p.c.b.mounting hole detail 线路板安装孔尺寸图

需要了解其它产品详细资料请直接电话（13928227597）或qq（632950171）旺旺（world walk）联系。

本产品的加工定制是否，品牌是WORLDWALK，型号是SL10NV(3.3)，种类是贴片式，用途是普通，材料是碳膜，性能是片式，阻值调节方式是直滑式，阻值变化方式是B，标称阻值是500~1M，额定功率是0.1（W），阻值允许偏差是 ± 10 （%），滑动噪声是47（V），分辨率是100（%），零位电阻是10（ Ω ），接触电阻是5（ Ω ），绝缘电阻是100（M Ω ），符合度是100