

T型头 欧式插拔头 T型插拔头 可分离/连接器

产品名称	T型头 欧式插拔头 T型插拔头 可分离/连接器
公司名称	浙江南鹏电气有限公司
价格	面议
规格参数	品牌:南鹏 型号:DFJQ15-630
公司地址	浙江 乐清市 北白象镇芝湾村
联系电话	057762736008

产品详情

djbk 12/14-630a欧式后接头

概述 general性能 features630a欧式后接头可和欧式前接头或另外的后接头连接，提供扩展的电缆连接回路(分支)，它不能直接和套管座、穿墙套管连接。其尾部可直接用绝缘塞堵塞，也可扩展连接另一路欧式后接头或后接避雷器。630a t back connector can be use together with the t fore connector and someother back connector, it can be provide more branches, and they can not together withthe bushing directly, cover the back protection cap on the end of the blanking cover.当与适合的套管或插头配合时，提供全屏蔽和全封闭可分离连接；可长期在水下和其他恶劣的条件下运行；内置式电容测试点用以测定线路带电状态或安装带电指示器；无最小相间安全距离要求；安装可以是垂直、水平或任意角度。provides a fully screened and fully submersible separable connection when matedwith the proper busing or plug.can be used under the circumstances.built-in capacitive test point to determine the ciecuit status or install a fault indicator.no minimum phase clearance requirements.mounting can be vertical, horizontal, or any angle in between.标准包装 scope of delivery产品装箱参数 packange Information3只/盒 重量：6.08kg 体积：30cm × 25cm × 22cm3 pcs/box w/g: 6.08kg vol: 30cm × 25cm × 22cm630a欧式后接头本体黑色防尘帽（非绝缘保护帽）应力锥压接端子连接铜棒双头螺栓硅脂、清洁纸安装指导说明书产品合格证t back connectorcovering capadaptorconductor cable lugconnect lugtwo head screwsilicone lubricant、ciewing paperinstallation Instruction sheetquality certi?cate

产品构造product structure

双头螺栓：不锈钢螺栓确保导体和套管紧密配合。绝缘层：特有的配方和混合技术确保预制epdm绝缘橡胶的优质品质。绝缘子：环氧树脂绝缘子内含有带螺纹金属件可以确保与双头螺栓紧密配合。电容测试

点：电容测试点用于测试线路是否带电。测试点盖：预制的epdm导电测试点盖保护测试点并在正常运行中将其接地。内半导体层：预制的epdm导电橡胶有效的控制电气应力。应力锥：不同尺寸的应力锥配合电缆接头使用，能确保水密封以及电缆应力释放。接地眼：预注到外屏蔽中用于接地线的连接。外半导体层：预制的epdm导电橡胶与电缆屏蔽层搭接使屏蔽连续，并确保外半导体层处于接地状态。压接端子：全铜或铜铝接端子适用于铜或铝导体。two head screw: to make sure have a good contact with the apparatus bushing.insulation: moulded epdm insulating rubber is formulated and mixed in-house to ensure high quality.insulating plug: molded epoxy insulating plug provides excellent electrical, thermal and mechanical reliability.test point(optional): corrosion-resistant, conductive electrode provides consistent capacitive voltage for application of fault indicators and determining a circuit's state.test point cover: a moulded epdm conducting rubber cap provides a watertight seal and check circuit status.semi-conductive insert: moulded epdm conducting rubber screen control electrical stress.stress relief: the configuration of the outer screen and the cable adapter provide cable stress relief.grounding eye: moulded into the external screen for connection of an earthing wire.semi-conductive shield: moulded epdm conducting rubber mates with the cable screen to maintain screen continuity and ensure that the assembly is at earth potential.conductor cable lug: aluminum compression connector is sized to ensure a cool running connector with maximum current transfer.

本产品的加工定制是是，品牌是南鹏，型号是DFJQ15-630，类型是欧式电缆分接箱，外壳材质是硅橡胶，额定电压是15（KV），额定电流是0.63（KA），适用范围是电缆分接箱的进出线连接