

LCR测试仪 LCR-8101 南京 无锡

产品名称	LCR测试仪 LCR-8101 南京 无锡
公司名称	南京海纳仪器设备有限公司
价格	面议
规格参数	类型: 品牌:Gwinstek/固纬 型号:LCR-8101
公司地址	南京市雨花台区钱家村2号1203室
联系电话	52405707 13655177297

产品详情

Icr-8101|Icr测试仪|台湾固纬insteck主要技术指标

5位量测分辨率

Icr-8101|Icr测试仪|台湾固纬insteck详细技术指标

特点

test frequency 20hz ~ 1 mhz
6 digit measurement resolution
dc resistance measurement
monitoring of dut voltage and current
0.1% basic measurement accuracy
comprehensive measurement functions
pass/fail test
rs-232 & gpib interface
large lcd display

test frequency

20hz ~ 1mhz, 5 digits, ± 0.005%

input impedance

100

basic accuracy

± 0.1% (r, z, x, g, y, b, l, c)

test speed

ac

max: 75ms

fast: 150ms

medium: 450ms

slow: 600ms

dc

max: 30ms

fast: 60ms

medium: 120ms

slow: 500ms

test signal levels

10mv~2vrms, 1mv/step, ± 2.5%

short circuit current

max. 20ma

measurement ranges

r, z, x	0.1m ~ 1m
g, y, b	10ns ~ 1ks
	0.1nh ~ 100kh
c	0.001pf ~ 1f
d	0.0001 ~ 9.9999
q	0.1 ~ 9999.9
rdc	0.1m ~ 100m

measurement parameters

impedance (z), phase angle (), inductance (l), capacitance (c), ac resistance (rac), quality factor (q), dissipation factor (d), admittance (y), conductance (g), reactance (x), susceptance (b), dc resistance (rdc)

series or parallel equivalent circuit

c + r, c + d, c + q, l + r, l + q

series equivalent circuit only

x + r, x + d, x + q

parallel equivalent circuit only

c + g, b + g, b + d, b + q

polar form

z + phase angle, y + phase angle

Lcd display

320 x 240 dot-matrix

interface

rs-232, gpib

power source

ac 115v/230v (selectable), 50/60hz

accessories

user manual x1, power cord, test lead lcr-06a x 1

dimensions & weight

330(w) x 170(h) x 340(d)mm, approx. 5kg

本产品的类型是LCR测试仪，品牌是Gwinstek/固纬，型号是LCR-8101