

DS-820配合多种计量装置 大型立式全自动包装机主机

产品名称	DS-820配合多种计量装置 大型立式全自动包装机主机
公司名称	中山市大森包装机械有限公司
价格	面议
规格参数	功能:充填,杀菌、干燥,计量,条码识别、打印,包装容器成型,打码、喷码,裹包 品牌:大森
公司地址	中国 广东 中山市 火炬开发区宫花村牌坊侧D幢三楼
联系电话	86 0760 89937376 18607601392

产品详情

主要性能与结构特点(function and structure characteristics)

1. 采用彩色触摸屏和稳定可靠的双轴高精度输出的plc控制、制袋、计量、充填、封合、打码、切袋一次性完成。(plc control with stable & reliable biaxial high accuracy output and color touch screen, bag-making, measuring, filling, printing, cutting, finished in one operation.)
2. 气路控制和电路控制电箱独立分离, 噪音小, 电路更稳定。(separate circuit boxes for pneumatic control and power control. noise is low, and the circuit is more stable.)
3. 采用双皮带伺服拉膜: 拉膜阻力少, 包装袋成型好, 更美观, 皮带不易磨损。(film-pulling with servo motor double belt: less pulling resistance, bag is formed in good shape with better appearance, belt is resistant to be worn-out.)
4. 采用伺服控制, 实现高精度定位, 尺寸准确。(double servo control, high precision orientation, size more nicety.)
5. 采用外置式放膜机构, 包装膜安装更简单、更容易。(external film releasing mechanism: simpler and easier installation of packing film.)
6. 包装袋的偏差调整只需在触摸屏上调整即可, 操作简单。(adjustment of bag deviation just needed to be controlled by the touch screen. operation is very simple.)
7. 整机采用封闭式机构, 有效防止粉尘进入机器内部。(close down type mechanism, defending powder into inside of machine.)

适用范围(scope or application)

适用于各种测量设备，包装不同种类的(suitable for many kinds of measuring equipment,and package different kinds of)

选配装置(optional device)

真空拉膜机构 插角机构 托料装置 连袋装置 (vacuum film pulling mechanism inserted angle mechanism material supportingdevice connected bag device)

技术参数 (technique specification)

机型 (type)	ds-820
制袋长度(bag length)	100-400mm(l)
制袋宽度(bag width)	180-400mm(w)
薄膜宽度(max width of roll film)	820mm
包装速度(packing speed)	5-30bags/min
计量范围(measuring range)	6000ml (max)
气压(air consumption)	0.65mpa
耗气量(gas consumption)	0.4m ³ /min
电压 (power voltage)	220vac/50hz
功率 (power)	5kw
外型尺寸 (dimension)	(l)1780 × (w)1350 × (h)1950mm
机器重量 (wight of machine)	900kg

本产品的加工定制是是，功能是充填,杀菌、干燥,计量,条码识别、打印,包装容器成型,打码、喷码,裹包，品牌是大森，型号是DS-820主机，电压是220（V），功率是5（Kw），包装膜宽是820（mm），制成袋尺寸是L(100~400)XW(180~400)（mm），包装速度是5~30（袋/分钟），重量是900（kg），外形尺寸是(L)1780 × (W)1350 × (H)1950（mm），包装材料是复合材料，包装类型是袋，自动化程度是全自动，适用对象是谷物,配合多种计量装置，可包装不同种类的物料，适用行业是餐饮,食品,化工,日化,医药，物料类型是固体，售后服务是主机一年保修（易耗件除外），规格是计量范围：6000ml(Max)