## 成都调味品-醋灌装机-食用油灌装机

产品名称	成都调味品-醋灌装机-食用油灌装机	
公司名称	邛崃市临邛镇四信设备门市	
价格	面议	
规格参数	种类:调味品包装机械 品牌:四信机械	
公司地址	四川 邛崃市 临邛镇三好社区十二组	
联系电话	2888742966 18982217290	

## 产品详情

该灌装机是一种由微电脑(plc)可编程控制,光电传感,气动执行于一体的高新技术灌装设备。本机型专用于食品类,如:白酒、酱油、醋、调味品、植物油、糖浆、矿泉水等可食性液体以及农药化工类液体的灌装。灌装计量精确,无气泡、无滴漏。可适用于50-1000ml各种瓶型(包括异型瓶)的灌装。

## 一、先进的设计

该机适用于不同规格容器的灌装,可在数分钟内切换灌装规格。

灌装周期短、生产能力高。 更换灌装规格无需增添备件,只需作调整即可完成。 用户可根据自己的生产能力选择灌装数量确定灌装头数。 触摸式操作彩屏,可显 示生产状况、操作程序、灌装方式等。画面直观、操作简单、维护方便。

每个灌装头设有卡瓶口设置、确保注料对位准确。二、独特的灌装方式设计选用直线式分组进瓶、出瓶的方式、使灌装功能扩展,各种形状的容器、都能在本设备有效灌装。 选用国际先进的气体灌装阀,确保灌装过程无滴漏、无垂涎。强大的plc软件支持,可实现理想的灌装作业。

人机友好界面,所有操作均在触摸式彩屏上完成。三、精确的计量控制 灌装采用固定流道参数,控制灌装时间来实现不同计量的灌装。 气动阀灌装的精 确时间可设定到0.01秒,能使计量精确度控制在±1%误差范围,减少不必要的物 料损耗,提高用户经济效益。

每个灌装头的计量可以进行单独调整,以实现灌装计量的一致。 本机设定了进瓶技术程序、无瓶、计数不到位不灌装,只有当计数器记录到的瓶数与设定的灌装瓶数一致时才开始灌装。 灌装量的多少,可以进行初调到所需灌装量时,再进行微调,即可得到理想的灌装计量精度。四、技术参考

序号	型 号	zhga-2	zhza-4	zhga-6	zhga-8	zhga-10	zhga-12
1	灌装头数	2	4	6	8	10	12
	/	100 - 10000ml					
3	生产能力(瓶/小时)	350-500	600-1000	1000-1500	1500-2200	1600-2200(5 瓶计)	1800-260
							(5 瓶计)
						<u> </u>	

4	灌装精度	0.5%	
5	电源	50hz/60hz 3n-380v ± 10%	
6	功 耗	0.75kw-7.5kw	
7	配用气源压力	0.5-0.8mpa	
8	工作压力	0.6-0.7mpa	
初船	「网址・www 88742966 com		

this machine is one kind by the microcomputer (plc) programmable control, the photoelectricity sensing, the air operated execution fills in a body high technology and new technology installs the equipment. the this aircraft uses in food class specially, for example: white liquor, soy sauce, vinegar, seasoning, vegetable oil, syrup, mineral water and so on edibility the liquids as well as the agricultural chemicals chemical industry class liquid fills the attire. fills installs the measurement to be precise, does not have the air bubble, does not have the dripping of a water clock. suitably (including leads bottle) fills the attire in 50-1000ml each kind of bottle.

the advanced designthis machine is suitable in the different specification vessel fills the attire, may cut in several minutes fills installs the specification fills installs the cycle short, productivity is high the replacement fills installs the specification not to need to increase the spare parts, only must make the adjustment then to complete the user may act according to own productivity choice to fill installs quantity to determine fills the pattern number.the touching type operation colored tablet, may demonstrate the production condition, the operation sequence, fill install the way and so on, the picture direct-viewing, the operation simple, the maintenance is convenient each fills the pattern to be equipped with the card bottle mouth establishment, to guarantee the note material to be accurate to the position. unique fills installs the waydesign to select the straight line type to group the bottle, the bottle way, causes to fill installs the function to expand, each kind of shape vessel, all can fill the attire effectively in this equipment selects the international advanced gas to fill installs the valve, guarantees fills installs the process not to have the dripping of a water clock, not to drool the formidable plc software support, may realize ideally fills installs the work, the man-machine friendly contact surface, all operations complete on the touching type colored tablet.

the precise measurement controlfills the attire to use the fixed flow channel parameter, the control fills installs the time to realize the different measurement to fill the attire the pneumatic valve fills the precise time which installs to be possible to establish to 0.01 second, can cause the measurement precision control at  $\pm$  1% erroneous scope, reduces the nonessential material loss, enhances the user economic efficiency each fills the pattern the measurement to be possible to carry on the independent control, realizes fills installs the measurement the consistency the this aircraft established has entered the bottle technology procedure, does not have the bottle, the counting does not arrive does not fill the attire, only then when the counter recorded the bottle number filled the bottling number consistently with the hypothesis when only then starts to fill the attire fills the load how many, may carry on when initially moves must fill the load, again carries on the trimming, then obtains ideally fills installs the measuring accuracy.

the technical referencefills installs the scope 50~1000 milliliters to fill installs the speed <90 bottle/the minute (refers to 100~500 milliliters scopes) to measure the precision ± 1%rated power 0.8 kilowattworking voltage 220 voltwork barometric pressure 6~7 kilograms/square centimetergas consumption 0.5 cubic meter/minutemachine net

本产品的加工定制是是,种类是调味品包装机械,品牌是四信机械,净重是550(kg),售后服务是保修 1年,保质期是120,售卖方式是包装,特产是是