# 防爆三防灯|机械化工矿山业IP66三防灯|FB系重工业抗摔耐压三防灯

| | |
|---|---|
| 产品名称 | 防爆三防灯|机械化工矿山业IP66三防灯|FB系重工业抗摔耐压三防灯 |
| 公司名称 | 深圳市鼎城威电子科技有限公司 |
| 价格 | 面议 |
| 规格参数 | 型号:HHSF-FB240<br>防护等级:IP66 |
| 公司地址 | 深圳市宝安区石岩街道水田社区宝石东路268号-3伟兴科技园A栋厂房1-6层（六层西） |
| 联系电话 | 0755-81732129 13902920910 |

# 产品详情

description:

the enclosures of full plastic explosion-proof ( emergency ) fluorescent light fittings (pole m
ounting) are manufactured by glass fiber reinforced polyester and the transparent parts are
manufactured by anti-ultraviolet polycarbonate. they have good protection ability from various
chemical matters in factories because of high stability and mechanical strength. the material
of the light fitting used can prevent from being corroded effectively. the sealing bars bet
ween the enclosure and transparent parts are compacted by the interlock device. the isolatio
n switches are operated by the interlock devices. when the isolation switch is switched off,
the covers can be opened. the explosion-proof electronic ballast, explosion-proof
isolation switch, explosion-proof lamp holder and explosion-proof terminals etc are mounted
inside of the full plastic explosion-proof fluorescent light fittings (pole mounting).
the explosion-proof electronic ballast, explosion-proof inverter, explosion-proof fuse, explosion-p
roof indicator lamp, and high temperature resistance explosion-proof battery etc. are mounted
inside of the full plastic explosion-proof emergency fluorescent light fittings .the light fitting
can be automatically recharging while normal working, so that the lamp tube will turn
on automatically when the power loses because of accident or power failure. ▲ full plasti
c explosion-proof fluorescent light fittings mounting ways: ceiling type, chain type, pendant t
ype, wall type and clamp type. ▲ full plastic explosion-proof fluorescent li
ght fittings mounting ways: platform fence type, platform flange type, street lamp type. ●st
andard two-supply circuit design and eol switching off function design when the life of th
e lamp tube is end; ●the structural design is never distortion and its protection degree i
s up to ip66. ●equipped with the mechanical interlocking device and explosion-proof distan
ce switch of ii c class to enable the power off automatically when the diffuser is uncov
ered. ●with interlock device, the transparent parts and enclosure can not energize to work
to ensure safe use before completely sealing. ●the explosion-proof ballast and explosion-pr
oof inverter are certified separately; ●the explosion-proof ballast is equipped with the protect
ive functions of open circuit, short circuit and abnormity of lamp tube; ●the emergency
type has the indication of fault signal, the charging signal, the discharging signal.

cz0865/cz0866

full plastic explosion-proof fluorescent light with or without emergency

main technical data:

ex mark: ex deq iic t4/t5

intended use:  can be used in zone 1, zone 2, zone 21 and zone 22

ambient temperature: -25℃≤ ta ≤ 40℃

degree of protection: ip66

lamp: fluorescent tube

potency: 1 or 2x14/18w; 1 or 2x 28/36w

rated voltage: ac110 ~ 240v( + 10%), 50/60hz

lamp holder type: g13 two-pin

power factor: e.o.l. protection > 0.98

emergency: 1.5h up to 3h

cable entry: m25 x 1.5mm2

本产品的加工定制是否，型号是HHSF-FB240，防护等级是IP66，光源类型是LED灯，光源功率是2*40（W），电压是220（V），外形尺寸是1270（mm），主要适用范围是机械化工矿山等重工业