



p2/22、zb-jvp3vp3/22、zb-jvplvpl22、zb-jvp1vrp1、zb-djypv、zb-djypvr、zb-djyrvp、zb-djyp2v、zb-djyp2vr、zb-djyp3v、zb-djyp3vr、zb-djyplv、zb-djyvp、zb-djyvrp、zb-djyvp2、zb-djyvp3、zb-djyvpl、zb-djyvpr、zb-djyvp2r、zb-djypv22、zb-djyvp22、zb-djyvrp22、zb-djyvp2/22、zb-djyvrp2/22、zb-djyvp3/22、zb-djyvpl22、zb-djyvrp3、zb-djyvrpl、zb-djypv、zb-djypvr、zb-djyrvp、zb-djyp2v、zb-djyp2vr、zb-djyp3v、zb-djyp3vr、zb-djvplv、zb-djvvp、zb-djvvrp、zb-djvvp2、zb-djvvp3、zb-djvvpl、zb-djvvpr、zb-djvvp2r

本产品的加工定制是是，型号是WDZNB-DJFP2YP2、WDZC-DJVFYP、WDLB-DJVYP2-32，品牌是0550-7516696，芯数是2-42，护套材质是聚氯乙烯，聚乙烯，材料形状是圆线，拉伸强度是国标，电线最大外径是38（mm），绝缘厚度是2.2（mm），产品认证是准产证