

伊萨DS9000-B3 药芯焊丝

| | |
|------|--------------------------|
| 产品名称 | 伊萨DS9000-B3 药芯焊丝 |
| 公司名称 | 上海钰泰焊接材料有限公司 |
| 价格 | 100.00/公斤 |
| 规格参数 | 品牌:齐全 型号:DS9000-B3 |
| 公司地址 | 上海市浦东新区川沙路500号205-248室 |
| 联系电话 | 021-31263590 13818577790 |

产品详情

| 规格型号 | 品名 | 直径 | 包装 |
|--------------|-------|-----|-----|
| ds7100 ultra | 药芯焊丝 | 1.2 | 15 |
| ds7100 ultra | 药芯焊丝 | 1.4 | 15 |
| ds7100 ultra | 药芯焊丝 | 1.6 | 300 |
| ok12.60tr | tig焊条 | 2.4 | 5 |
| ok16.10tr | 不锈钢焊条 | 2.0 | 5 |
| ok16.10tr | 不锈钢焊条 | 2.4 | 5 |
| ok16.12mw | 不锈钢焊丝 | 1.2 | 15 |
| ok16.30tr | 不锈钢焊条 | 1.6 | 5 |
| ok16.30tr | 不锈钢焊条 | 2.0 | 5 |
| ok16.30tr | 不锈钢焊条 | 3.2 | 5 |
| ok16.32mw | 不锈钢焊丝 | 1.2 | 15 |
| ok16.53tr | 不锈钢焊条 | 1.6 | 5 |
| ok16.53tr | 不锈钢焊条 | 2 | 5 |

| | | | |
|------------|-------|-----|------|
| ok16.53tr | 不锈钢焊条 | 2.4 | 5 |
| ok16.53mw | 不锈钢焊丝 | 1.2 | 12.5 |
| ok63.30 | 手工焊条 | 2.5 | 10.2 |
| ok48.04 | 焊条 | 2.5 | 20 |
| ok48.04 | 焊条 | 3.2 | 20 |
| ok13.22tr | 焊条 | 2.4 | 5 |
| ok10.71saf | 焊剂 | | 25 |
| ok10.81saf | 焊剂 | | 20 |
| e316l-17 | 手工焊条 | 2.4 | 20 |
| e316l-17 | 手工焊条 | 3.2 | 20 |
| e316l-17 | 手工焊条 | 4 | 20 |
| e308l-17 | 手工焊条 | 3.2 | 20 |
| e308l-17 | 手工焊条 | 2.4 | 20 |
| e308l-17 | 手工焊条 | 4 | 20 |
| e309l-17 | 手工焊条 | 2.4 | 20 |
| e309l-17 | 手工焊条 | 3.2 | 20 |
| er4043 | 铝焊丝 | 1.2 | 7.3 |
| er4043 | 铝焊丝 | 1.6 | 7.3 |
| r4043 | 铝焊条 | 2.4 | 4.56 |
| r4043 | 铝焊条 | 3.2 | 4.56 |
| r4047 | 铝焊条 | 2.4 | 4.56 |
| r4047 | 铝焊条 | 3.2 | 4.56 |
| er5183 | 铝焊丝 | 1.2 | 7.3 |
| r5356 | 铝焊条 | 2.4 | 4.56 |
| r5356 | 铝焊条 | 3.2 | 4.56 |
| | | | |

| | | | |
|-----------------|---------|-----|------|
| er5356 | 铝焊丝 | 1.2 | 7.3 |
| er5356 | 铝焊丝 | 1.6 | 7.3 |
| sb316l | 不锈钢药芯焊丝 | 1.6 | 12.5 |
| m316l | 不锈钢药芯焊丝 | 1.2 | 12.5 |
| m316l | 不锈钢药芯焊丝 | 1.6 | 12.5 |
| t309l | 不锈钢焊条 | 2 | 5 |
| pw 6010 | 焊条 | 3.2 | 16 |
| ds8000-b2 | 药芯焊丝 | 1.2 | 15 |
| ds9000-b3 | 药芯焊丝 | 1.2 | 15 |
| e309l | 焊条 | 3.2 | 5 |
| ok13.29 | 焊丝 | 1.2 | 30 |
| ok76.18 | 焊条 | 2.5 | 9 |
| ok76.18 | 焊条 | 3.2 | 11.4 |
| ok76.28 | 焊条 | 2.5 | 9 |
| ok76.28 | 焊条 | 3.2 | 12 |
| ok55.00 | 焊条 | 2.5 | 20 |
| 12.51mw | 焊丝 | 1.2 | 250 |
| sw10p | 焊条 | 3.2 | 22.7 |
| sw10p | 焊条 | 4 | 22.7 |
| sw810p | 焊条 | 4 | 22.7 |
| spoolarc 65 | 焊丝 | 2.4 | 4.5 |
| er80s-b2 | 焊丝 | 2.4 | 4.5 |
| er90s-b2 | 焊丝 | 2.4 | 4.5 |
| coreshield 8nil | 焊丝 | 2 | 25 |

低碳钢焊接材料

| 种类 | esab 牌号 | 技术标准 | | 熔敷金属 | |
|----------|-----------------|---------------|-------------------------------------|--------|---------|
| | | sfa/aws | en | 屈服值mpa | 抗拉强度mpa |
| 手工 焊条 | ok 43.32 | a5.1 e6013 | en499 e 42 0 rr 12 | 460 | 550 |
| | ok 46.00 | a5.1 e6013 | en499 e 38 0 rc 11 | 400 | 510 |
| | ok 46.16 | a5.1 e7014 | en499 e 38 0 rc 11 | 440 | 505 |
| | ok 48.04 | a5.1 e7018 | en499 e 42 4 b 32 h5 | 480 | 560 |
| | ok 48.05 | a5.1 e7018 | en499 e 42 4 b 42 h5 | 445 | 540 |
| | ok 48.15 | a5.1 e7018 | en499 e 42 3 b 32 h5 | 490 | 575 |
| | ok 48.18 | a5.1 e7018-1 | en499 e 42 5 b 32 h10 | 490 | 575 |
| | ok 48.30 | a5.1 e7018 | en499 e 42 4 b 42 h10 | 460 | 550 |
| | ok 48.68 | a5.1 e7018-1 | en499 e 42 5b 42 h5 | 470 | 560 |
| | ok 50.10 | a5.1 e6013 | en499 e38 2 a 12 | 430 | 500 |
| | ok 50.40 | a5.1 e6013 | en499 e 42 2 rb 12 | 450 | 540 |
| | ok 53.05 | a5.1 e7016 | en499 e 42 5 b 12 | 470 | 540 |
| | ok 53.35 | a5.1 e7048 | en499 e 42 4 b 35 h5 | 460 | 560 |
| | ok 53.68 | a5.1 e7016-1 | en499 e 42 5 b 12 h5 | 460 | 550 |
| | ok 53.70 | a5.1 e7016-1 | en499 e 42 5 b 12 h5 | 440 | 530 |
| | ok 55.00 | a5.1 e7018-1 | en499 e 46 5 b 32 | 480 | 590 |
| 气保 | ok autrod 12.50 | a5.18 er70s-6 | en440 g 38 2 c g3si1 g 42 3 m g3si1 | 440 | 540 |

| | | | | | |
|------|-----------------|----------------------------|---|--|-----|
| 焊丝 | ok autrod 12.51 | a5.18 er70s-6 | en440 g 38 2 c g3si1 g 42 3 m g3si1 | 470 | 560 |
| | ok autrod 12.63 | a5.18 er70s-6 | en440 g 42 2 c g4si1 g 46 3 m g4si1 | 525 | 595 |
| | ok autrod 12.64 | a5.18 er70s-6 | en440 g 42 2 c g4si1 g 46 3 m g4si1 | 525 | 595 |
| 药芯焊丝 | ok tubrod 14.11 | a5.18-93 e70c-6m h4 | en 758(1997) t 42 4 m m 3 h5 | 470 | 560 |
| | ok tubrod 15.00 | a5.20-95 e715t-5, e715t-5m | en 758:1997 t 42 3 b c 2 h5 t 42 3 b m 2 h5 | 470 | 550 |
| | ok tubrod 15.14 | a5.20-95 e71t-1 e71t-1m | en 758:1997 t 46 2 p m 2 h10 t 46 2 p c 2 h10 | 530 | 580 |
| | ok tubrod14.00s | a5.17-89 f7a2-ec1 | | 450 | 530 |
| | ok tubrod15.00s | a5.17-89 f7a4-ec1 | | 430 | 540 |
| 氩弧焊丝 | ok tigrod 12.60 | a5.18 er70s-3 | en 1668 w2si | 420 | 515 |
| | ok tigrod 12.61 | a5.18 er70s-6 | en 1668 w3si1 | 470 | 560 |
| | ok tigrod 12.64 | a5.18 er70s-6 | en 1668 w4si1 | 525 | 595 |
| 埋弧焊丝 | ok autrod 12.10 | a5.17 el12 | en 756 s1 | 配用焊剂 ok flux 10.40, 10.45, 10.82, 10.83, 10.96 | |
| | ok autrod 12.20 | a5.17 em12 | en 756 s2 | 配用焊剂 ok flux 10.40, 10.45, 10.71, 10.80, 10.81, 10.82, 10.83 | |
| | ok autrod 12.22 | a5.17 em12k | en 756 s2si | 配用焊剂 ok flux 10.45, 10.61, 10.82, 10.83 | |
| | ok autrod 12.30 | | en 756 s3 | 配用焊剂 ok flux 10.40, 10.70, 10.82, 10.83 | |
| | ok autrod 12.32 | a5.17 eh12k | en 756 s3si | 配用焊剂 ok flux 10.40, 10.61, 10.82, 10.83 | |
| | ok autrod 12.40 | a5.17 eh14 | en 756 s4 | 配用焊剂 ok flux 10.62 | |