

# 印刷机 水性印刷机 水墨印刷机

产品名称	印刷机 水性印刷机 水墨印刷机
公司名称	东光县立飞包装机械有限公司
价格	面议
规格参数	柔印机类型:机组式 印刷颜色:彩印
公司地址	东光县连镇镇李四维村
联系电话	03177751098 13700372085

## 产品详情

ykw系列全自动高速水性印刷开槽模切机	
ykw-series automatic high-speed plexo printing slotting die-cutter	
送纸部	印刷部
模切部	开槽部
功能与特点：	
<p>电脑调整，换单更快，操作方便。 整机墙板、重要部件，均由高精度加工中心制做，数控磨床研磨而成。 所有传动轴、辊材质均为优质钢，高精度动平衡校正，镀硬铬、表面研磨。 传动齿轮材质为20crmnti合金钢，渗碳淬火处理，硬度为hrc58-62研磨而成，长期使用，套色精度高。 整机主要传动部位，采用免键连接环，消除连接间隙，适合长期高速印刷。 整机喷淋式润滑，附设机油自动平衡装置。 自动归零，自动复位。 pclick控制网络、mcgs软件、西门子低压电器，主机变频控制，省电达30%。 双轴开槽配置整机生产管理电脑控制系统，单轴开槽配置整机电脑控制系统。 选装远程电脑诊断系统。</p>	
computer order storage and convenient operation.	主要技术参数 (main technical parameters)
complete machine wallboard and other important pieces are all made by high precision process center and grinded by digit-controlled grinder.	单位 unit
steel with high-precision dynamic balance, plated with rigid chrome and grinded surface.	2800型 2800型
参数名称 wyazs name	

<p>adopts the high-quality steel, which is grinded after heat-treatment, after 1500g, 2500 still 1500x2700 the high topping          最大过纸面积max paper transmission parts adopt the hand-free connection ring to eliminate the interval,          suitable for long-term high speed printing. the whole machine undergoes the spray lubrication and is equipped</p>				
<p>with engine oil automatic balance facilities. it possesses the print, die 500x1200, slotting 500x2400 function, which          有效印刷面积effective printing area. plink control network, mcgs software, siemens low voltage electric          appliance and host frequency conversion control, 30% electricity saving. double axle slotting to configure</p>				
<p>whole machine production management computer control system and 400x500 slotting 400x500 configure whole machine          最小加工尺寸minimust size control system optional: remote computer diagnosis system</p>				
<p>印刷版厚度thickness of printing plank</p>	mm	6	6	
<p>最高速度(片/分)max speed</p>	pieces/min	120	120	
<p>经济速度(片/分)economy speed</p>	pieces/min	100	100	
<p>主电机变频功率frequency conversion power of main motor</p>	kw	18.5-30	18.5-30	
<p>套色精度(四色)topping precision(four colors)</p>	mm	± 0.75	± 0.75	
<p>开槽精度slotting precision</p>	mm	± 1.5	± 1.5	

本产品的加工定制是是，柔印机类型是机组式，印刷颜色是彩印，操作方式是自动，适用对象是纸质包装，适用材质是纸板，品牌是立飞，产品类型是全新