

塑料磨平机 UL规格试料磨平机 PVC塑料磨平机 试料磨平机

产品名称	塑料磨平机 UL规格试料磨平机 PVC塑料磨平机 试料磨平机
公司名称	东莞市虎门品诚检测仪器设备厂
价格	面议
规格参数	品牌:顺成 型号:SC-7028
公司地址	东莞市虎门镇白沙五村工业区
联系电话	0769-81688951 15362623915

产品详情

本机在将橡胶或塑胶哑铃状试片磨平、磨薄或磨出所需之厚度，以供拉力、老化、耐油等试验之用。试片台左右、上下及前后之移动，以扳手操作。

符合ul1581标准第420.6条规定。

buffing machine (august 2, 2006 - ul 1581)

420.6 a power-driven buffing machine (grinding wheel) is appropriate for buffing irregularities from the samples from which die-cut specimens are to be prepared. the abrasive wheel is to be of about no. 36 grit (particle size of 0.019 inch or 0.486 mm). the wheel is to run true and is not to vibrate. the diameter of the wheel is not specified; however, 4-3/4 – 6-1/4 inch or 0.12 – 0.16 m has been found appropriate. the rotary velocity of the wheel is to be 2500 – 3500 r/min. the diameter and rotary velocity of the wheel are to be selected to give the wheel a peripheral speed (rpm × π × wheel diameter) of 3000 – 5000 ft/min or 15 – 25 m/s. caution – the maximum wheel diameter stated in this paragraph and the maximum wheel rpm stated in this paragraph shall not be used together as this combination will result in a peripheral speed above 5000 ft/min or 25 m/s. this applies even for wheels that are marked as being intended for a peripheral speed above 5000 ft/min or 25 m/s. the machine is to have a slow feed that applies light pressure and removes very little material at one cut, thereby not overheating the specimen or the wheel.

主要技术参数

砂 轮：36#；φ 100mm

砂轮线速度：3000 ~ 5000feet/min或15 ~ 25m/s

皮帶輪加速比：2：1

體 積：50 × 60 × 40cm

重 量：50kg

電 源：1 ， ac220v 50hz

本產品的加工定制是是，品牌是順成，型號是SC-7028，測量範圍是6AWG以上電線，磨擦頻率是4000~5000英尺/分，測量行程是10（mm），機台尺寸是500 × 600 × 400（mm）