

2010系列高防爆性能，微型保险丝

产品名称	2010系列高防爆性能，微型保险丝
公司名称	东莞市陆德电子有限公司
价格	面议
规格参数	加工定制：是： 型号：2010:种类：保险丝 用途：电子:体积：微型
公司地址	中国 广东 东莞 塘厦镇环市西路258号C栋708
联系电话	86-76988004582 13751368525

产品详情

一级经销商

product characteristics

materials body : thermoplastic ul94 v-0 lead : tinned copper wire operating temperature -55 to + 125 (consider de-rating) solder ability 260 , 3s. (wave) 350 ± 10 , 1s. (soldering iron) resistance to soldering heat 260 , 10s. (wave) , 350 , 3s. (soldering iron) recommended soldering parameters wave soldering parameter : soldering pot temperature :260 max solder dwell time : 2 5s hand welding parameter : soldering iron temperature : 350 ± 5 solder dwell time : 1 2s max. storage conditions can be stored for 3 years under tight seal condition at temperature of +10 ~60 , relative humidity 75%. at most can be kept 30 days at temperature +10 ~60 , relative humidity 95% under covered conditions

i-t characteristics
ampere rating% of ampere rating
opening time
100ma~6.3a
150%
210%
275%
400%
1000%

in accordance with iec60127-3 standard,sheet4

electrical characteristics	rated current	voltage rating	breaking capacity	safety approvals	approved /	pending
100ma	250v		100a@250v			
125ma	250v		ac&130a@2			
160ma	250v		50v ac			
200ma	250v					
250ma	250v		50a@250v ac			
315ma	250v					
400ma	250v					
500ma	250v					
630ma	250v					
800ma	250v					
1.00a	250v					
1.25a	250v					
1.60a	250v					
2.00a	250v					
2.50a	250v					
3.15a	250v					
4.00a	250v					
5.00a	250v					
6.30a	250v					

remark: for ,,,,130a at 250v ac and 100a at 250v ac;. for,,,50a at 300vac
for , 100a at 300v ac

本产品的加工定制：是是品牌：WALTERFUSE，型号：2010是种类：保险丝，用途：电子是体积：微型，电压特性：低压是形状：插片式，熔断速度：T/慢速是执行标准：欧规，自动复位功能：无是最大电压：300（V），最大电流：6.3（A）是保持电流：0.25-6.3（A），动作温度：-40-125（ ）