

SC镍氢电池 SY/申远

产品名称	SC镍氢电池 SY/申远
公司名称	江门市蓬江区胜宇电子有限公司
价格	面议
规格参数	品牌:SY/申远 型号:镍氢
公司地址	江门市蓬江区杜阮镇杜阮区龙田村
联系电话	13709614744 13702289499

产品详情

江门市胜宇电源科技有限公司是一家专业从事研发、生产和销售各种型号镍氢、镍镉电池厂，公司座落于美丽富裕的广东省江门市，比邻港、澳、珠三角，水陆交通十分便利。公司拥有一批长期稳定的研发、生产管理人才。公司技术力量雄厚，设备完善；品质体系严格，能为

客户提供优质、稳定的产品。

公司电池产品品种齐全，组合电池型式多样，并可按客户要求设计加工。产品具有容量高、内阻低，一致性好，循环寿命长，放电平台稳定等优点，产品广泛应用于电子礼品、应急照明、无绳电话、电蚊拍、电动玩具、剃须刀、自动报警系统等等。公司奉行“以客为先，以质为本”的品质政策，“诚信经营，以人为本”的管理理念，使公司得到了国内外客户的一致认同。我们愿以最大的热情和努力，与客户共同发展，携手共创美好的未来。

使用寿命：

胜宇电池能够充放电循环500次以上容量不少于80%，使得它更加经济实效，而且其使用的时间与预期的时间保持一致。

优良的放电特性：

胜宇电池具有种类齐全、容量高、功率大（内阻小）、自放电小、1小时快速充电、寿命长和一致性好等特点，同时也可以满足客户对电池高、低温特殊性能的要求。

储存寿命：

储存时间长，且限制条件少，它允许长时间储存后自由放电，能够在广泛的范围内使用。

温度范围广：

即使在低温范围内，放电特性也是优越的，电池在高温环境下的使用，显示了高效的充放电性能及长时间的使用寿命，而且在某些应用上更是可以达到70摄氏度。

可靠的安全阀：

每个电池都装备了可靠稳定的安全阀，在长时间使用过程中提供了高度的可靠性。

电池的存放的注意事项：

- 1、 请将电池储存在阴凉，干燥场所。
- 2、 长期存放（如6个月以上）应该用小电流充放电3次，以恢复到饱和容量。
- 3、 在电池充满或半满的状态下，不要将大量的电池密集存放。
- 4、 在储存或运输电池时不要将金属物体与电池混放在一起，以防止意外的短路。

胜宇不断开发新产品、新技术、新工艺和增添新设备使电池的产品种类齐全、性能优异、品质均一。

以客为先、以质为本、诚信经营、以人为本、客户的需求就是我们胜宇的行动指南。

交货准时快捷，服务细致周到。

能够对所有单体电池进行焊接组合加工及oem包装加工。

不同的产品需要不同的电池型号组合，欢迎来电咨询了解！

detailed product description

ni-cd rechargeable battery packs1)rechargeable battery packs2)with ce approved3)high capacity4)good quality & low price

ni-cd rechargeable battery packs

1)batteries size: aaa, aa, a, sc, c, d, f2)nominal voltage: 1.2v per unit cell

3)capacity: 200mah-8, 000mah4)suitable for cordless phone, flashlight, tools, l/c toys, emergency light etc.5)different combinations are available6)different connectors and wires are available7)oem/odm orders are welcome

8)long service life and low impedance9)good storage characteristics and rapid charge compatible

10)little memory effort and environment friendly

our batteries are suitable for many areas such as calculators, power tools, tape recorders, flashlights, medical devices (e.g., defibrillators), electric vehicles, space applications. please see the following pictures:

specification of ni-cd batteries:

table1: charge/discharge chemical reactions

operational battery voltage	0.9 to 1.5 volts
specific energy	30 to 40 wh/kg
energy density	85 to 100 w/l
power density	100 to 150 w/kg
continuous rate capability	typical: 3c high rate: 10c
pulse rate capability	up to 25c
cycle life at 100% dod	typically 500
calendar life	3 - 5 years
self discharge rate	25% /month
operable temperature	-20 celsius to 60 celsius
memory effect	yes

note: characteristics can change according to improvements in chemistry or special niche requirements.

designation for battery packs and some connector models:

about us:

we are the manufactura specialize in all kinds of ni-mh and ni-cd batteries. you can get more information from our website: www.jmshengyu.cn which introduce our company in details or contact us for more information. we only make the best quality batteries. our products have been exported to all over the world and have won warm praise from all our customers because of our good quality and reasonable price.

本产品的加工定制是是，品牌是SY/申远，型号是镍氢，充电时间是60（h），外型尺寸是12*13*0.1（mm），充电电流是90%（A），标准电压是1.2V（V），额定容量是1500（mah），产品认证是ROHS