

型号	额定容量 (kva)	相数	频率 (hz)	额定输入电压 (v)	额定输出电压 (v)	负载电流 (a)	空载电流(a)	总损耗(w)	外形尺寸
tsja-10	10	三相	50	380	0-650	8.9	3	650	90
					0-500	11.5	3.5	800	
					0-380	15.2	4	1000	
					0-250	23	5	1300	
tsja-20	20	三相	50	380	0-650	17.8	4.6	1180	90
					0-500	23	5.5	1300	
					0-380	30.4	7.5	1500	
					0-250	46	10	1700	
tsja-30	30	三相	50	380	0-650	26.6	6.8	1650	98
					0-500	34.6	8.5	1800	
					0-380	45.6	10	2000	
					0-250	69	12	2200	
tsja-50	50	三相	50	380	0-650	45	10.3	2360	98
					0-500	58	11	2500	
					0-420	69	12	2600	
					0-380	76	12.5	2800	
					0-300	96	12.8	3000	
					0-250	115	13	3150	
tsja-63	63	三相	50	380	0-650	56	12.5	2800	111
					0-500	73	13.5	3050	
					0-420	87	15	3300	
					0-380	96	16	3500	
					0-300	121	17	3800	
					0-250	145	19	4000	
tsja-75	75	三相	50	380	0-650	67	15.5	3300	111
					0-500	87	16.5	3550	
					0-420	103	17	3800	
					0-380	114	18	4000	
					0-300	144	19	4250	
					0-250	173	20	4500	
tsja-100	100	三相	50	380	0-650	88.8	19	4000	111
					0-500	115.5	20	4250	
					0-420	137.5	21	4500	
					0-300	192.5	23	5050	
					0-250	230	24	5300	
tsja-125	125	三相	50	380	0-650	111	23	4750	128
					0-500	144	25	5050	
					0-420	172	27	5300	
					0-380	190	28	5600	
					0-300	240	29	6000	
tsja-150	150	三相	50	380	0-250	288.7	30	6350	128
					0-650	133	22	4750	
					0-500	173	27	5450	
					0-420	206	31	6100	
					0-380	228	33.5	6650	
tsja-160	160	三相	50	380	0-300	289	34.5	7300	128
					0-250	346	36	7800	
					0-650	142	28	5600	

				0-500	185	30	6000
				0-420	220	33	6350
				0-380	243	34	6700
				0-300	308	35	7300
				0-250	369.5	36	7900
tsja-200	200			0-650	178	34.5	6700
				0-500	231	36.5	7300
				0-420	275	40.5	7900
				0-380	304	42.5	8500
				0-300	385	43	8900
				0-250	462	44	9400

本产品的电压比是0-430，电源相数是三相，防潮方式是开放式，冷却方式是油浸自冷式，冷却形式是液/油浸式，频率特性是中频，品牌是STO，绕组形式是自耦，铁心形式是环形，铁心形状是环型，外形结构是立式，效率()是90%，型号是TSJA油浸式感应稳压器，加工定制是是，应用范围是调压