

法国阿酷司I-acoustics K2线阵音响

产品名称	法国阿酷司I-acoustics K2线阵音响
公司名称	广州番禺慧通音响器材厂
价格	.00/件
规格参数	法国阿酷司:35 Hz - 20 kHz (K2:147 dB ([K2_70] 预设) 法国:H × V: 70 ° / 90 ° / 1
公司地址	广州市番禺区南村镇市新公路北段103号
联系电话	13342871528

产品详情

Usable bandwidth (-10dB) 35 Hz - 20 kHz

Maximum SPL1 147 dB ([K2_70] preset)

Coverage angle (-6 dB) Horizontal: 110 ° / 70 ° symmetric ; 90 ° asymmetric (35 ° / 55 ° or 55 ° / 35 °)

Vertical: depends on the number of elements and array curvature

Transducers LF: 2 x 12 ' ' , weather-resistant, bass-reflex

MF: 4 x 6.5 ' ' , weather-resistant, bass reflex

HF: 2 x 3 ' ' , diaphragm compression driver, DOSC waveguide

Nominal impedance LF: 2 x 8 ohms MF: 8 ohms HF:16 ohms

RMS power handling LF: 2 x 450 W MF: 320 W HF: 160 W

Connectors IN: 1 x 8-point PA-COM LINK: 1 x 8-point PA-COM

Rigging components Captive 4-point rigging system

Inter-enclosure angles: 0.25, 1, 2, 3, 4, 5, 7.5 or 10 °

Physical data

W/w x H x D 1338 x 354/286 x 400 mm 52.7 x 14/11.3 x 15.8 in

Weight (net) 56 kg 123.2 lb.

Cabinet First grade Baltic birch plywood

Side panels Die cast aluminum

Finish Dark Grey brown Pantone 426C

Front Steel grill with anti-corrosion coating Airnet acoustically neutral fabric

Protection rating IP45

Rigging components High grade steel with anti-corrosion coating