

DQ900拖拉机 农用拖拉机

| | |
|------|----------------------------------|
| 产品名称 | DQ900拖拉机 农用拖拉机 |
| 公司名称 | 泰安市大牛农机有限责任公司 |
| 价格 | .00/个 |
| 规格参数 | 拖拉机类型:农用拖拉机 品牌:DQ 型号:DQ900 |
| 公司地址 | 岱宗大街404号 |
| 联系电话 | 0538-2115588 13953801536 |

产品详情

| | | | |
|-------|--|------|-----------------------|
| 拖拉机类型 | 农用拖拉机 | 品牌 | DQ |
| 型号 | DQ900 | 产品类型 | 全新 |
| 机器大小 | 大型 | 档数 | 8F + 2R |
| 发动机型号 | LRC4108T LRC4108T 4MC4110 LRC4108ZT | 轮胎规格 | 2195 |
| 额定功率 | 62.5 (Kw) | 结构重量 | 3570 (kg) |
| 生产厂家 | 烟台东汽农业装备有限公司 | 外型尺寸 | 4593X2050X2810 (mm) |

main specifications of dq804,854,904,954

| | | |
|----------------------------|---------|--------------------|
| tractorparameters 拖拉机参数 | model型号 | dq804 /854/904/954 |
|----------------------------|---------|--------------------|

| | | |
|-------------------------------|--|---|
| | drive type驱动形式 | 4wd |
| | overall dimensionlxwxh(mm)外型尺寸：长x宽x高 | 4593x2050x2810 |
| | wheel track(mm)轮距 | front前轮 1610-1950(leave factory 1610) rear后轮 1620-2020(leave factory 1620)1620 |
| | wheel base(mm)轴距 | 2195 |
| | min. distance from ground(mm)最小离地间隙 | 379(front drive axle under)379 (前) |
| | rated traction force(kn)标定牵引力 | 18.6/19.9/20.8/21.7 |
| | structure weight (kg) 结构质量 | with cabin带驾驶室 3820 without cabin不带驾驶室 3570 |
| | turning round radius(m)最小转向半径 (m) | without single break不单边制动 4.3 ± 0.3 |
| | theoretical speed(km/h)理论速度(km/h) | forward前进速度 2.31/34.85(general gear)/0.46-34.85(gear) 2.31/34.85(普通)/0.46-34.85 reverse (km/h)后退速度 3.1-10.78(general gear)/0.62-10.78(gear) 3.1-10.78(普通)/0.62-10.78 |
| enginespecifications 发动机参数 | model型号 | Irc4108t Irc4108t 4mc4110 Irc4108t |
| | type型式 | vertical put, four-stroke, water-cooled chamber水冷、直列、四冲程、 |
| | rated power(km)/rotation(r/min) 标定功率 (kw) 转速 (r/min) | 59/2300,62.5/2300,66/2300,73.5/2300 |
| | diesel consumption(g/km/h)柴油消耗率 | 242 |
| | machine oil consumption(g/km/h)机油消耗率 | 1.63 |
| | cylinder no.缸数 | 4 |
| drivesystem 传动系 | clutch离合器 | dual-stage cltch 双作用离合器 |
| | gear box变速箱 | 4x(2+1) general gear4x(2+1)x2 cre 4x(2+1)x2 爬行档 (选装) |
| | differential 差速器 | close type, 4 planetary bevel gear闭 |
| | differential lock差速锁 | joggle cover type啮合套式 |
| | final transmissions后最终传动 | single grade planetary bevel gear单 |

| | | | |
|------------------------------|--------------------------|--|--|
| travelling mechanism 行走系统 | tyre size 轮胎规格 | front前轮 | 11.2-24 |
| | | rear后轮 | 16.9-34/13.6-38(paddy field tyre) |
| | steering gear type 转向器型式 | | hydraulic steering 液压转向 |
| | driver brake 行驶制动器 | | disk type 盘式 |
| working device 工作装置 | hydraulic system 液压系统 | system max. lift capacity at 610mm of suspension point(kn) 系统最大提升力(kn) (悬挂后610mm处) | >16 |
| | | suspension model 悬挂机构 | rear, three-points suspension, cat |
| | p.t.o shaft 动力输出轴 | rotating speed(rpm) 转速 | 760/1000, 540/1000(optional) 760/ |
| | | spline size 齿形 | 35, 6 rectangular spline, 38 spline 35, 6齿矩形花键轴, 或 |