

GIICL14 鼓形齿式联轴器生产厂家

产品名称	GIICL14 鼓形齿式联轴器生产厂家
公司名称	镇江德瑞机械有限公司
价格	9000.00/套
规格参数	品牌:德瑞 型号:GIICL14
公司地址	江苏省镇江市镇扬路二摆渡北侧
联系电话	86-051188989206 13376165048

产品详情

型号	公称 转矩 tn kn.m	许用 转速 [n] r/mi n	轴孔 直径 d1,d2	轴孔长度 l		d	d1	d2	c	h	a	b	转动 惯量 kg.m ²	润滑 脂 用量 ml	质量 kg	
				y	j1											
g cl1	0.4	4000	16,18,19	42	—	103	71	50	8	2	36	76	0.0035	51	5.1	
			20,22,24	52	38										0.0035	3
			25,28	62	44										0.0035	3.1
			30,32,35	82	60										0.0038	3.6
g cl2	0.71	4000	20,22,24	52	—	115	83	60	8	2	42	88	0.0058	70	4.9	
			25,28	62	44										0.0055	4.5

			30,32,3 5,38	82	60								0.006		5.1	
			40,42,4 5	112	84								0.0068		6.2	
g	cl3	1.12	4000	22,24	52	—	127	95	75	8	2	44	90	0.0105	68	7.5
				25,28	62	44								0.01		7
				30,32,3 5,38	82	60								0.01		6.9
				40,42,4 5,48,50 55,56	112	84								0.0113		8.6
g	cl4	1.8	4000	38	82	60	149	116	90	8	2	49	98	0.02	87	10.1
				40,42,4 5,48,50 55,56	112	84								0.0223		12.2
				60,63,6 5	142	107								0.0245		14.5
g	cl5	3.15	4000	40,42,4 5,48,50 55,56	112	84	167	134	105	10	2.5	55	108	0.0378	125	16.4
				60,63,6 5,70,71 75	142	107								0.0433		19.6
g	cl6	5	4000	45,48,5 0,55,56	112	84	187	153	125	10	2.5	56	110	0.0663	148	22.1
				60,63,6 5,70,71 75	142	107								0.075		26.5
				80,85,9 0	172	132								0.0843		31.2
g	cl7	7.1	3750	50,55,5 6	112	84	204	170	140	10	2.5	60	118	0.103	175	27.6
				60,63,6 5,70,71 75	142	107								0.115		33.1

			80,85,9 0,95	172	132								0.1298		39.2	
			100,(1 05)	212	167								0.151		47.5	
g	cl8	10	3300	55,56	112	84	230	186	155	12	3	67	142	0.167	268	35.5
				60,63,6 5,70,71 ,75	142	107								0.188		42.3
				80,85,9 0,95	172	132								0.21		49.7
				100,11 0,(115)	212	167								0.241		60.2
g	cl9	16	3000	60,63,6 5,70,71 ,75	142	107	256	212	180	12	3	69	146	0.316	310	55.6
				80,85,9 0,95	172	132								0.356		65.6
				100,11 0,120,1 25	212	167								0.413		79.6
				130,(1 35)	252	202								0.47		95.8
g	cl1 0	22.4	2650	65,70,7 1,75	142	107	287	239	200	14	3.5	78	164	0.511	472	72
				80,85,9 0,95	172	132								0.573		84.4
				100,11 0,120,1 25	212	167								0.659		101
				130,14 0,150	252	202								0.745		119
g	cl1 1	35.5	2350	70,71,7 5	142	107	325	276	235	14	2.5	81	170	0.454	550	97
				80,85,9 0,95	172	132								1.096		114

			240,25 0,260	410	330								15.85		696
			280,(2 85)	470	380								17.45		786
g cl1 6	250	1300	200	352	282	580	522	430	28	7	209	354	23.925	4500	799
			240,25 0,260	410	330								26.45		913
			280,30 0,320	470	380								29.1		1027
g cl1 7	355	1200	250,26 0	410	330	644	285	490	28	7	198	364	43.095	4900	1176
			280,(2 90)300 ,320	470	380								47.525		1322
			340,36 0,(365)	550	450								53.725		1532
g cl1 8	500	1050	280,(2 90)300 ,320	470	380	726	654	540	28	8	22	430	78.525	7000	1698
			340,36 0,380	550	450								87.75		1948
			400	650	540								99.5		2278
g cl1 9	710	950	300,32 0	470	380	818	748	630	32	8	232	440	136.75	8900	2249
			340,(3 50),36 0,380,(390)	550	450								153.75		2591
			400,42 0,440,4 50,460, (470)	650	540								175.5		3026
g cl2 0	1000	800	360,38 0,(390)	550	450	928	838	720	32	11	247	470	261.75	11000	3384
			400,42 0,440,4	650	540								299		3984

			50,460													
			480,500													
			530,560,600	800	680								360.75		4430	
g	cl2	1400	750	400,420,440,450,460	650	540	1022	928	810	40	12	255	490	468.75	13000	4977
			480,500													
			530,560,600	800	680									561.5		6152
g	cl2	1800	650	450,460,480,500	650	540	1134	1036	915	40	13	262	510	753.75	16000	6318
			530,560,600,630	800	680									904.75		7738
			670, (680)	900	780											
g	cl2	2500	600	530,560,600,630	800	680	1282	117	1030	50	14	299	580	1517	28000	10013
			670, (700), 710,750, (770)	900	780									1725		11553
g	cl2	3550	550	560,600,630	800	680	1428	1322	1175	50	17	317	610	2486	33000	12915
			670, (700), 710,750	900	780									2838.5		15015
			800,850	1000	880									3131.8		16615
g	cl2	4500	460	670, (900	780	1644	1538	1390	50	19	325	620	5174.3	43000	19837

5		700), 710,75 0										
		800,85 0	1000	880						5836.5	22381	
		900,95 0	—	980						6413	24765	
		1000, (1040)	—	1100						7198.3	27797	

产品：联轴器

品牌：derek/德瑞

型号：鼓形齿式联轴器

规格：giicl14

工程转矩：112000n.m

许用转速：1650转/分

重量：450kg

性能介绍：齿式联轴器是有齿数相同的内齿圈和带外齿的凸缘半联轴器等零件组成。外齿分为直齿和鼓形齿两种齿形，所谓鼓形齿即为将外齿制成球面，球面中心在齿轮轴线上，齿侧较一般齿轮大，鼓形齿式联轴器可允许较大的角位移（相对于直齿联轴器），可改善齿的接触条件，提高传递转矩的能力，延长使用寿命。