

Supply LED displays

产品名称	Supply LED displays
公司名称	深圳市冬青光电有限公司
价格	5000.00/平方
规格参数	品牌:ARISE 型号:P1.8 P2.5 P3 P4 P5 P6 P7.62 P8.9 P10 P12P16 P20 P2
公司地址	Jingsheng Industry Area, Huafan Road, Dalang Street, Bao ' an District, Shenzhen,
联系电话	0755-66801409 13620209526

产品详情

full color dip led display

quick detail:

- (1) computer control with software
- (2) high resolution, top vision
- (3) show images, videos, texts, messages.....
- (4) 2-5 years warranty

features:

1. wide viewing angle:

110(h),110(v), it is 2 times wider than dip led on vertical angle, color becomes more natural,more efficient on information express,better advertising effect.

2. better waterproof:

it 's with 4 legs,same as dip led, which enable enough marine glue on facade of pcb to proof water, enduring for long time use,which is different from outdoor smd led.

3. high quality video performance:

one piranha led includes 3 colors, so the color mixing is better than dip led, same as smd led, quality of video performance optimized.

4. anti-uv

the encapsulation technique and epoxy resin of piranha led is different with smd, same as dip led, so it is durable for damage from ultraviolet rays. there is no color shifting for the piranha led after long time use.

about arise technology:

arise technology are the professional and famous manufacturer of led screen in shenzhen, china. we have exported to north america, europe, south america, middle east, central asia and many other areas of the world.

arise technology has more than 300 workers and a strong r&d team with 15 employees.

also arise technology has the dip, smt and other advanced equipments for high efficiency productions.

arise technology also has a professional qc team, they will double check all the quality details before delivery.

with high quality, good reputation and competitive price, arise technology is going to achieve more in the global market.

indoor p2.5 led display parameters	
model	f i-2.5
parameters	speci.
pixel pitch	2.5mm
pixel composition	1r1g1b
led type	3-in-1 smd2121 (high contrast black led)
display brightness	1000cd/m ² (adjustable)

color temperature	2500k to 10000k
viewing angle	h: 160 ° ; v:160 °
pixel density	160000 pixels/m ²
minimum viewing distance	2.5 m
module size	160mm × 160mm ; 160mmx80mm. two versions.
cabinet size	w480mm × h480mm × d90mm
cabinet weight	11.5 kg/cabinet
cabinet size	0.2304 m ²
cabinet material	iron
cabinet aspect ratio	1:1
cabinet resolution	192 × 192 pixels
grey scale	16bit (high refresh)、14bit (common refresh)
driving mode	1/16 scan, constant current
processing depth	65536 scales
colors	281.4 trillion
led wave length	r: 620~630nm g: 520~535nm b: 465~475nm
brightness control	manual/automatic

display contrast	5000:1
frame rate	50/60 hz
refresh rate	3200 hz (high refresh) 、 1000 hz(common refresh)
input voltage	110~220vac ± 15%
input power frequency	50~60 hz
max. power consumption	170w/cabinet
ave. power consumption	57w/cabinet
life span	100,000 hours
input signal	rf,s-video,rgbhv,yuv,yc & composition,etc
communication collection	cat5 cable: 140m; multi-mode fiber 500m; single mode fiber 20km)
installation method	hanging /wall mounted/other customized installation methods.
protection scale	ip43
operation humidity	0 ~+45 /10~90%rh
storage humidity	-10 ~+55 /10~90%rh