

# P10 Rental LED Display

产品名称	P10 Rental LED Display
公司名称	深圳市冬青光电有限公司
价格	.10/平方
规格参数	品牌:ARISE 型号:P1.8 P2.5 P3 P4 P5 P6 P7.62 P8.9 P10 P12P16 P20 P2
公司地址	Jingsheng Industry Area, Huafan Road, Dalang Street, Bao ' an District, Shenzhen,
联系电话	0755-66801409 13620209526

## 产品详情

arise technology co., ltd is a high-tech company dedicated in providing professional led displays and comprehensive optoelectronic solutions.

arise technology owns strong execution, brilliant development strategies and programs, sustainable creation based on market demand. we spare no effort to provide customers with market-oriented innovative products with good reliability, suitable solutions and all-round service. arise ' s main products includes indoor and outdoor led displays for fix installation, indoor and outdoor led displays for rental business, stadium perimeter led displays, and other special led displays in accordance with customized requirements; led display control system, related optoelectronic equipment, led devices and components. we are ready to providing led display solutions for oversea and domestic advertisement media, building advertising and lighting, municipal administration, hospital, hotel, bank, traffic, sports, entertainment, show, exhibition, etc.

we arise technology regards integrity in company staff, customers and suppliers as the enterprise foundations, market demands as the guide. we guarantee quality with profession and dedication and use enterprise culture to fill our brand. we keep striving, forging ahead, creating to provide customer with strong and unremitting support and backup.

outdoor p10 rental led display parameters

model rfo-10

parameters speci.

module pixel composition smd led

pixel pitch ( mm ) 10

module resolution ( w × h ) 32x16 pixels

module size ( mm ) 320 ( w ) × 160 ( h )

module weight ( kg ) 0.45

max consumption ( w ) 20w

cabinet module quantity ( wxh ) 2 × 4

cabinet resolution ( w × h ) 64x64

cabinet size ( mm ) 640 ( w ) × 640 ( h ) × 70 ( d )

cabinet area ( m<sup>2</sup> ) 0.4096

weight ( kg/cabinet ; kg/m<sup>2</sup> ) 16 ; 40

pixel density ( pixels/m<sup>2</sup> ) 10000

cabinet flatness ( mm ) 0.2

optics

single pixel brightness correction yes

single pixel color correction yes

white balance ( nits ) 6000

color temperature ( k ) 3200—9300 adjustable

horizontal viewing angle 160 °

vertical viewing angle 160 °

luminous point center distance deviation <3%

luminance uniformity 97%

chromaticity uniformity ± 0.003<sub>cx,cy</sub>之内

contrast

3000:1

power max. power consumption 360w/cabinet ; 900w/m2.

ave. power consumption 120w/cabinet ; 300w/m2.

power supply ac220v ( 50-60hz )

processing driving mode constant current drive

frame rate ( hz ) 60

refresh rate ( hz ) 2000

operation life span ( hrs ) 50,000

operation temperature ( ) -10 — 40

storage temperature ( ) -20 — 60

operation humidity ( rh ) 10 - 80%

storage humidity ( rh ) 10- 85%